



32501.002
09.01.02.0014

Florida Department of Environmental Regulation

Twin Towers Office Bldg. • 2600 Blair Stone Road • Tallahassee, Florida 32399-2400

Lawton Chiles, Governor

Virginia B. Wetherell, Secretary

June 8, 1993

N00204.AR.000572

NAS PENSACOLA

5090.3a

**CERTIFIED MAIL
RETURN RECEIPT REQUESTED**

Ms. Linda Martin
Department of the Navy
Southern Division - Code 1851
Naval Facilities Engineering Command
Post Office Box 10068
Charleston, South Carolina 29411-0068

Dear Ms. Martin:

Department personnel have completed the technical review of the Final Sampling and Analysis Plan, Category 111, Sites 2, 11, 30 and 38, NAS Pensacola. I have enclosed a memorandum addressed to me from Mr. Jorge R. Caspary. It documents our comments on the referenced report.

If I can be of any further assistance with this matter, please contact me at 904/488-0190.

Sincerely,

Eric S. Nuzie
Federal Facilities Coordinator

ESN/bb

Enclosure

cc: Jorge Caspary
Bill Kellenberger
Ron Joyner
Allison Drew
Satish Kastury
Lynn Griffin
John Mitchell



State of Florida
DEPARTMENT OF ENVIRONMENTAL REGULATION

For Routing To Other Than The Addressee	
To: _____	Location: _____
To: _____	Location: _____
To: _____	Location: _____
From: _____	Date: _____

Interoffice Memorandum

TO: Eric S. Nuzie, Federal Facilities Coordinator
Bureau of Waste Cleanup

THROUGH: Dr. James J. Crane, PG Administrator
Technical Review Section *JJC*

FROM: Jorge R. Caspary, PG I/Base Coordinator *JRC*
Technical Review Section

DATE: May 25, 1993

SUBJECT: Review of Final Sampling and Analysis Plans. Category
III Sites 2, 11, 30, and 38. Pensacola Naval Air
Station.

.....

I have reviewed the above mentioned documents and comments expressed on our February 26, 1993 letter have been addressed. Specifically, the Navy has agreed to conduct full-scale pumping tests where groundwater remediation is likely. Likewise, the Navy has clarified its position regarding soil sampling intervals: soil sampling intervals will be from 0.0-1.0 foot bgs, 1.0-3.0 feet bgs, etc to the water table as agreed during the July 14, 1992 RPM meeting. Also, and in accordance with Florida Administrative Code Chapter 40-A-3, the Navy will use neat cement grout during monitor well installations with any variance to this rule being requested from the North Florida Water Management District. Based on these changes, the workplans should be considered final.