

N00204.AR.004155
NAS PENSACOLA
5090.3a

HEALTH AND SAFETY PLAN FOR CONTAMINATION ASSESSMENT FUEL FARM
CONTAINING STORAGE TANKS 681 AND 682 REVISION 1 NAS PENSACOLA FL
7/1/2001
TETRA TECH

Health and Safety Plan
for
Contamination Assessment
at the
Fuel Farm Containing
Storage Tanks 681 and 682
Revision 1
Naval Air Station
Pensacola, Florida



Southern Division
Naval Facilities Engineering Command
Contract No. N62467-94-D-0888
Contract Task Order 0198

July 2001

**HEALTH AND SAFETY PLAN
FOR
CONTAMINATION ASSESSMENT
AT THE FUEL FARM CONTAINING
STORAGE TANKS 681 AND 682
Revision 1**

**NAVAL AIR STATION
PENSACOLA, FLORIDA**

**COMPREHENSIVE LONG-TERM
ENVIRONMENTAL ACTION-NAVY (CLEAN) CONTRACT**

**Submitted to:
Southern Division
Naval Facilities Engineering Command
2155 Eagle Drive
North Charleston, South Carolina 29406**

**Submitted by:
Tetra Tech NUS, Inc.
661 Andersen Drive
Pittsburgh, Pennsylvania 15222**

**CONTRACT NUMBER N62467-94-D-0888
CONTRACT TASK ORDER 0198**

JULY 2001

**PREPARED UNDER THE
SUPERVISION OF:**

**GERALD WALKER , P.G.
TASK ORDER MANAGER
TETRA TECH NUS, INC.
TALLAHASSEE, FLORIDA**

APPROVED FOR SUBMITTAL BY:



**MATTHEW M. SOLTIS, CIH, CSP
CLEAN HEALTH & SAFETY MANAGER
TETRA TECH NUS, INC.
PITTSBURGH, PENNSYLVANIA**

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1.0 INTRODUCTION.....	1-1
1.1 KEY PROJECT PERSONNEL AND ORGANIZATION.....	1-1
1.2 SITE INFORMATION AND PERSONNEL ASSIGNMENTS.....	1-3
2.0 EMERGENCY ACTION PLAN	2-1
2.1 INTRODUCTION	2-1
2.2 PRE-EMERGENCY PLANNING	2-1
2.3 EMERGENCY RECOGNITION AND PREVENTION	2-2
2.3.1 Recognition	2-2
2.3.2 Prevention	2-3
2.4 SAFE DISTANCES AND PLACES OF REFUGE	2-3
2.5 EVACUATION ROUTES AND PROCEDURES	2-3
2.6 EMERGENCY ALERTING AND ACTION/RESPONSE PROCEDURES	2-3
2.7 EMERGENCY CONTACTS	2-4
2.8 EMERGENCY ROUTE TO HOSPITAL	2-5
2.9 DECONTAMINATION PROCEDURES/EMERGENCY MEDICAL TREATMENT	2-7
2.10 ILLNESS/INJURY REPORTING	2-7
3.0 SITE BACKGROUND	3-1
3.1 SITE DESCRIPTION	3-1
4.0 SCOPE OF WORK	4-1
5.0 TASKS/HAZARDS/ASSOCIATED CONTROL MEASURES SUMMARIZATION	5-1
6.0 HAZARD ASSESSMENT	6-1
6.1 CHEMICAL HAZARDS	6-1
6.2 PHYSICAL HAZARDS	6-1
6.2.1 Heavy Equipment Hazards.....	6-2
6.2.2 Energized Systems	6-2
6.2.3 Ambient Temperature Extremes	6-3
6.3 NATURAL HAZARDS	6-3
6.3.1 Insect/Animal Bites and Stings.....	6-3
6.3.2 Inclement Weather.....	6-4
7.0 AIR MONITORING	7-1
7.1 INSTRUMENTS AND USE	7-1
7.1.1 Photoionization Detector or Flame Ionization Detector	7-1
7.1.2 Hazard Monitoring Frequency.....	7-1
7.2 INSTRUMENT MAINTENANCE AND CALIBRATION.....	7-1

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
8.0 TRAINING/MEDICAL SURVEILLANCE REQUIREMENTS	8-1
8.1 INTRODUCTION/REFRESHER/SUPERVISORY TRAINING	8-1
8.1.1 Requirements for TtNUS Personnel	8-1
8.1.2 Requirements for Subcontractors	8-1
8.2 SITE-SPECIFIC TRAINING	8-3
8.3 MEDICAL SURVEILLANCE	8-3
8.3.1 Medical Surveillance Requirements for TtNUS Personnel	8-3
8.3.2 Medical Surveillance Requirements for Subcontractors	8-5
8.3.3 Requirements for All Field Personnel	8-5
8.4 SUBCONTRACTORS EXCEPTIONS	8-5
9.0 SITE CONTROL	9-1
9.1 EXCLUSION ZONE	9-1
9.1.1 Exclusion Zone Clearance	9-1
9.2 CONTAMINATION REDUCTION ZONE	9-2
9.3 SUPPORT ZONE	9-2
9.4 SAFE WORK PERMITS	9-2
9.5 SITE VISITORS	9-4
9.6 SITE SECURITY	9-4
9.7 SITE MAP	9-5
9.8 BUDDY SYSTEM	9-5
9.9 MATERIAL SAFETY DATA SHEETS (MSDS) REQUIREMENTS	9-5
9.10 COMMUNICATION	9-5
10.0 SPILL CONTAINMENT PROGRAM	10-1
10.1 SCOPE AND APPLICATION	10-1
10.2 POTENTIAL SPILL AREA	10-1
10.3 LEAK AND SPILL DETECTION	10-1
10.4 PERSONNEL TRAINING AND SPILL PREVENTION	10-1
10.5 SPILL PREVENTION AND CONTAINMENT EQUIPMENT	10-2
10.6 SPILL CONTROL PLAN	10-2
11.0 CONFINED SPACE ENTRY	11-1
12.0 MATERIALS AND DOCUMENTATION	12-1
12.1 MATERIAL TO BE POSTED AT THE SITE	12-1
13.0 GLOSSARY	13-1
ATTACHMENT I – ILLNESS/INJURY PROCEDURE AND REPORT FORM	
ATTACHMENT II – TICK CONTROL AND LYME DISEASE	
ATTACHMENT III – EQUIPMENT INSPECTION CHECKLIST	
ATTACHMENT IV – SAFE WORK PERMITS	
ATTACHMENT V - HEAT STRESS	

TABLES

<u>Section</u>	<u>Page</u>
2-1 Emergency Contacts	2-5
5-1 Tasks/Hazards/Control Measures Compendium	5-3
6-1 Chemical, Physical and Toxicological Data	6-5

FIGURES

<u>Section</u>	<u>Page</u>
2-1 Hospital Route	2-6
2-2 Emergency Response Protocol.....	2-8
7-1 Documentation of Field Calibration	7-3
8-1 Training Letter	8-2
8-2 Site-Specific Training Documentation	8-4
8-3 Subcontractor Medical Approval Form	8-6
8-4 Medical Surveillance Letter	8-8
9-1 Safe Work Permit.....	9-3

1.0 INTRODUCTION

This Health and Safety Plan (HASP) has been written to encompass investigation activities that are to be conducted at the Fuel Farm containing Storage Tanks 681 and 682 (Fuel Farm) at Naval Air Station Pensacola (NAS Pensacola), Pensacola, Florida as part of Contract Task Order (CTO) 0198. Specifically, this HASP addresses the contamination assessment activities to be conducted to determine the nature and extent of releases of petroleum constituents at the Tank Farm. This HASP is being prepared for NAS Pensacola as part of an overall effort conducted under Comprehensive long-term Environmental Action Navy (CLEAN III) administered through the U.S. Navy Southern Division Naval Facilities Engineering Command (NAVFAC), as defined under Contract Number N62467-94-D-0888. In addition to the HASP, a copy of the Tetra Tech NUS, Inc. (TtNUS) Environmental Health and Safety Guidance Manual must be present at the site during the performance of site activities. The Guidance Manual provides supporting information pertaining to the HASP, as well as TtNUS Standard Operating Procedures (SOP's). Both documents must be present at the site to comply with the requirements stipulated in the Occupational Safety and Health Administration (OSHA) standard 29 CFR 1910.120.

This HASP has been developed using the latest available information regarding known or suspected chemical contaminants and potential physical hazards associated with the proposed work and site. The HASP will be modified, if new information becomes available. All changes to the HASP will be made by the Project Health & Safety Officer (PHSO) and approved by the TtNUS CLEAN Health and Safety Manager (HSM) and the Task Order Manager (TOM). The TOM will notify affected personnel of all changes.

1.1 KEY PROJECT PERSONNEL AND ORGANIZATION

This section defines responsibility for site safety and health for TtNUS and subcontractor employees engaged in onsite activities. Personnel assigned to these positions will exercise the primary responsibility for all onsite health and safety. These persons will be the primary points of contact for any questions regarding the safety and health procedures and the selected control measures that are to be implemented for onsite activities.

- The TtNUS TOM is responsible for the overall direction of health and safety for this project.
- The PHSO is responsible for developing this HASP in accordance with applicable OSHA regulations. Specific responsibilities include:

- i. Providing information regarding site contaminants and physical hazards associated with the site.
 - ii. Establishing air monitoring and decontamination procedures.
 - iii. Assigning personal protective equipment based on task and potential hazards.
 - iv. Determining emergency response procedures and emergency contacts.
 - v. Stipulating training requirements and reviewing appropriate training and medical surveillance certificates.
 - vi. Providing standard work practices to minimize potential injuries and exposures associated with hazardous waste work.
 - vii. Modify this HASP, as it becomes necessary.
- The TtNUS Field Operations Leader (FOL) is responsible for implementation of the HASP with the assistance of an appointed SSO. The FOL manages field activities, executes the work plan, and enforces safety procedures as applicable to the work plan.
 - The SSO supports site activities by advising the FOL on all aspects of health and safety on site. These duties may include:
 - i. Coordinates all health and safety activities with the FOL.
 - ii. Selects, applies, inspects, and maintains personal protective equipment.
 - iii. Establishes work zones and control points in areas of operation.
 - iv. Implements air monitoring program for onsite activities.
 - v. Verifies training and medical clearance of onsite personnel status in relation to site activities.
 - vi. Implements Hazard Communication, Respiratory Protection Programs, and other associated health and safety programs as they may apply to site activities.
 - vii. Coordinates emergency services.
 - viii. Provides site-specific training for all onsite personnel.
 - ix. Investigates all accidents and injuries (see Attachment I - Illness/Injury Procedure and Report Form)
 - x. Provides input to the PHSO regarding the need to modify, this HASP, or applicable health and safety associated documents as per site-specific requirements.
 - Compliance with the requirements stipulated in this HASP is monitored by the SSO and coordinated through the TtNUS CLEAN HSM.

Note: In some cases one person may be designated responsibilities for more than one position. For example, at NAS Pensacola the FOL may also be responsible for SSO duties. This action will be performed only as credentials, experience, and availability permits.

1.2 SITE INFORMATION AND PERSONNEL ASSIGNMENTS

Site Name: Naval Air Station Pensacola Address: Pensacola, Florida

Navy Engineer-in-Charge: Byas Glover Phone Number: (843) 820-5651

Navy Environmental Coordinator: Greg Campbell Phone Number: (850) 452-4611 ext. 103

Purpose of Site Visit: This activity is divided into a multi-task operation (see Section 4.0), including soil boring (drilling), multi-media sampling, and other related activities.

Proposed Dates of Work: July 2001 through completion

Project Team:

TtNUS Personnel:

Gerald Walker, P.G.

TBD

Matthew M. Soltis, CIH, CSP

Clyde J. Snyder

TBD

Discipline/Tasks Assigned:

Task Order Manager (TOM)

Field Operations Leader (FOL)

CLEAN Health and Safety Manager (HSM)

Project Health and Safety Officer (PHSO)

Site Safety Officer (SSO)

Non-TtNUS Personnel

TBD

TBD

Affiliation/Discipline/Tasks Assigned

Drilling Subcontractor(s)

Hazard Assessment (for purposes of 29 CFR 1910.132) for HASP preparation has been conducted by: Clyde J. Snyder

TBD - To be determined

2.0 EMERGENCY ACTION PLAN

2.1 INTRODUCTION

This section has been developed as part of a preplanning effort to direct and guide field personnel in the event of an emergency. In the event of onsite emergencies that cannot be handled by onsite personnel, they will be evacuated to a safe place of refuge, and the appropriate emergency response agencies will be notified. Because a majority of potential emergency situations will require assistance from outside emergency responders, TtNUS and subcontractor personnel will not provide emergency response support for significant emergency events beyond responding to easily-controlled minor incidents. The emergency response agencies listed in this plan are capable of providing the most effective response and are designated as the primary responders. These agencies are located within a reasonable distance from the area of operations, a factor that ensures adequate emergency response time. This emergency action plan conforms to the requirements of OSHA Standard 29 CFR 1910.38(a), as allowed in OSHA 29 CFR 1910.120(l)(1)(ii).

TtNUS will, through necessary services, include initial response measures for incidents such as:

- Incipient fire-fighting support and prevention
- Incipient spill control and containment measures and prevention
- Removal of personnel from emergency situations
- Provision of initial medical support for injury/illness requiring only first-aid level support
- Provision of site control and security measures as necessary

2.2 PRE-EMERGENCY PLANNING

Through the initial hazard/risk assessment effort, injury or illness resulting from exposure to chemical or physical hazards or fire are the most probable emergencies that can be encountered during site activities. To minimize and eliminate these potential emergency situations, pre-emergency planning activities associated with this project include the following. The SSO and/or the FOL are responsible for:

- Coordinating response actions with NAS Pensacola Emergency Services personnel to ensure that TtNUS emergency action activities are compatible with existing facility emergency response procedures.

- Establishing and maintaining information at the project staging area (support zone) for easy access in the event of an emergency. This information includes the following:
 - Chemical Inventory (for substances used onsite), with Material Safety Data Sheets.
 - Onsite personnel medical records (medical data sheets).
 - A logbook identifying personnel onsite each day.
 - Emergency notification phone numbers in all site vehicles
- Identifying a chain of command for emergency action.
- Educating site workers to the hazards and control measures associated with planned activities at the site, and providing early recognition and prevention, where possible.

It is the responsibility of the TtNUS FOL to ensure that this information is available and present at the site.

2.3 EMERGENCY RECOGNITION AND PREVENTION

2.3.1 Recognition

Foreseeable emergency situations that may be encountered during site activities will generally be recognizable by visual observation. A clear knowledge of the signs and symptoms of overexposure to contaminants of concern may alert personnel of the potential hazards concerning themselves or their fellow workers. These potential hazards, the activities with which they have been associated, and the recommended control methods are discussed in detail in sections 5.0 and 6.0 of this document. Additionally, early recognition will be supported by periodic site surveys to eliminate any conditions that may predispose site personnel or properties to an emergency. The FOL and the SSO will constitute the site evaluation committee responsible for these periodic surveys. Site surveys will be conducted at least once a week during the initiation of this effort.

The above actions will provide early recognition for potential emergency situations. Should an incident take place, TtNUS will take defensive and offensive measures to control these situations. However, if the FOL and/or the SSO determine that an incident has progressed to a serious emergency situation, TtNUS will withdraw, and notify the appropriate response agencies.

2.3.2 Prevention

TtNUS and subcontractor personnel will minimize the potential for emergencies by ensuring compliance with the HASP, the Health and Safety Guidance Manual, applicable OSHA regulations, and through periodic site surveys of work areas.

2.4 SAFE DISTANCES AND PLACES OF REFUGE

In the event that the site must be evacuated, all personnel will immediately stop activities and report to the FOL at the place of safe refuge. Safe places of refuge will be determined prior to commencement of site activities and will be conveyed to personnel as part of the daily safety meeting conducted each morning. Upon reporting to the refuge location, personnel will remain there until directed otherwise by the TtNUS FOL. The FOL or the SSO will take a head count at this location to confirm the location of all site personnel. The site logbook will be used to take the head count. Places of refuge will ideally be selected which offer a point for communication purposes should this be required.

2.5 EVACUATION ROUTES AND PROCEDURES

Once an evacuation is initiated, personnel will proceed immediately to the designated place of refuge, unless doing so would further jeopardize the welfare of workers. In such event, personnel will proceed to a designated alternate location (to be identified) and remain there until further notification from the FOL. The use of these locations as assembly points provides communication and a direction point for emergency services, should they be needed.

Evacuation procedures will be discussed prior to the initiation of any work at the site. This shall include identifying primary and secondary evacuation routes and assembly points. Evacuation routes from the site are dependent upon the location at which work is being performed and the circumstances under which an evacuation is required. Additionally, site location and meteorological conditions (i.e., wind speed and direction) will influence the designation of evacuation routes. As a result, assembly points at NAS will be selected, and in the event of an emergency, field personnel will proceed to these points by the most direct route possible without further endangering themselves.

2.6 EMERGENCY ALERTING AND ACTION/RESPONSE PROCEDURES

Since TtNUS personnel will not always be working in the proximity of each other, hand signals, voice commands, air horns, and two-way radios (approved by NAS personnel) will comprise the mechanisms to alert site personnel of an emergency.

If an incident occurs, site personnel will initiate the following procedures:

- Initiate incident alerting procedures (if needed) verbally, by air horn, or using two-way radios.
- Evacuate non-essential personnel.
- Initiate incipient response procedures.
- Describe to the FOL (who will serve as the Incident Commander) what has occurred in as much detail as possible.

In the event that site personnel cannot control the incident through offensive and/or defensive measures, the FOL and/or the SSO will enact emergency notification procedure to secure additional outside assistance in the following manner:

- Call 911 for outside emergency service and report the emergency to the NAS Pensacola Emergency Dispatch - (850) 452-3333 (See Table 2-1)
- Give the emergency operator the location of the emergency and a brief description of what has occurred.
- Stay on the phone follow the instructions given by the operator
- The appropriate agency will be notified and dispatched

If an incident occurs at NAS Pensacola outside of designated operating areas impacting field personnel, the following procedures are to be initiated:

- Initiate an evacuation (if needed) by voice commands, hand signals, air horns, or two-way radio.
- Call Navy On-Site Representative
- Proceed to the assembly points as directed by NAS Pensacola personnel.

2.7 EMERGENCY CONTACTS

Prior to initiating field activities, all personnel will be thoroughly briefed on the emergency procedures to be followed in the event of an accident. Table 2-1 provides a list of emergency contacts and their associated telephone numbers. This table must be posted where it is readily available to all site personnel. Facility maps should also be posted showing potential evacuation routes and designated meeting areas.

**TABLE 2-1
EMERGENCY CONTACTS
NAS PENSACOLA**

AGENCY	TELEPHONE
EMERGENCY (outside services) (Police, Fire, and Ambulance Services)	911
NAS Pensacola - Emergency Dispatch	(850) 452-3333
Navy Engineer-in-Charge Byas Glover	(843) 820-5651
Navy Environmental Coordinator Greg Campbell	(850) 452-4611 ext. 103
Navy Hospital (Emergency Care only)	(850) 505-6600
Baptist Hospital (Non-emergency Care)	(850)469-2313
TtNUS Tallahassee Office and Task Order Manager (Gerald Walker)	(850) 385-9899
CLEAN Health and Safety Manager Matthew M. Soltis, CIH, CSP	(412) 921-8912
Project Health and Safety Officer Clyde J. Snyder	(412) 921-8904
Work Care	1-800-455-6155

2.8 EMERGENCY ROUTE TO HOSPITAL

For emergency care only, non-Navy personnel are permitted to go to the Navy Hospital.

Navy Hospital
Highway 98
Pensacola, Florida
(850) 505-6600

Directions to the Navy Hospital from the site are as follows:

Proceed out of NAS Main Gate (Navy Blvd) heading north to US Highway 98. Turn left (heading west) on US 98 and proceed approximately 1 mile. Hospital will be on the right (Building 2268).

A map indicating the travel route from the site to the Navy Hospital will be inserted as Figure 2-1.

Baptist Hospital (850-469-2313) will be used for all non-emergency care services. Directions to this Hospital are:

Proceed out of NAS Main Gate (Navy Blvd) heading north to Hwy 292. Turn right (heading east) on Hwy 292 until it turns into Garden Street (approx. 3 miles). Take Garden Street to intersection with "E" Street. Turn left onto "E" Street and proceed approximately 1 mile to Hospital on left.

FIGURE 2-1
Route to Hospital

2.9 DECONTAMINATION PROCEDURES/EMERGENCY MEDICAL TREATMENT

During any site evacuation, decontamination procedures will be performed only if doing so does not further jeopardize the welfare of site workers. Decontamination will not be performed if the incident warrants immediate evacuation. However, it is unlikely that an evacuation would occur which would require workers to evacuate the site without first performing the necessary decontamination procedures.

TtNUS personnel will perform removal of personnel from emergency situations and may provide initial medical support for injury/illnesses requiring only first-aid level support. Medical attention above that level will require assistance and support from the designated emergency response agencies. **If the emergency involves personnel exposures to chemicals, follow the steps provided in Figure 2-2.**

2.10 INJURY/ILLNESS REPORTING

If any TtNUS personnel are injured or develop an illness as a result of working on site, the TtNUS "Injury/Illness Procedure" (Attachment I) must be followed. Following this procedure is necessary for documenting all of the information obtained at the time of the incident. Also, as soon as possible Navy contact Ron Joyner must be informed of any incident or accident that requires medical attention.

Any pertinent information regarding allergies to medications or other special conditions will be provided to medical services personnel. This information is listed on Medical Data Sheets filed onsite. If an exposure to hazardous materials has occurred, provide information on the chemical, physical, and toxicological properties of the subject chemical(s) to medical service personnel.

FIGURE 2-2 EMERGENCY RESPONSE PROTOCOL

The purpose of this protocol is to provide guidance for the medical management of injury situations.

In the event of a personnel injury or accident:

- Rescue, when necessary, employing proper equipment and methods.
- Give attention to emergency health problems -- breathing, cardiac function, bleeding, and shock.
- Transfer the victim to the medical facility designated in this HASP by suitable and appropriate conveyance (i.e. ambulance for serious events)
- Obtain as much exposure history as possible (a Potential Exposure report is attached).
- If the injured person is a Tetra Tech NUS employee, call the medical facility and advise them that the patient(s) is/are being sent and that they can anticipate a call from the WorkCare physician. WorkCare will contact the medical facility and request specific testing which may be appropriate. WorkCare physicians will monitor the care of the victim. Site officers and personnel should not attempt to get this information, as this activity leads to confusion and misunderstanding.
- Call WorkCare at 1-800-455-6155 and enter Extension 109, or follow the voice prompt for after hours and weekend notification, and be prepared to provide:
 - Any known information about the nature of the injury.
 - As much of the exposure history as was feasible to determine in the time allowed.
 - Name and phone number of the medical facility to which the victim(s) has/have been taken.
 - Name(s) of the involved Tetra Tech NUS, Inc. employee(s).
 - Name and phone number of an informed site officer who will be responsible for further investigations.
 - Fax appropriate information to WorkCare at (714) 456-2154.
- Contact Corporate Health and Safety Department (Matt Soltis) at 1-800-245-2730.

As data is gathered and the scenario becomes more clearly defined, this information should be forwarded to WorkCare.

WorkCare will compile the results of all data and provide a summary report of the incident. A copy of this report will be placed in each victim's medical file in addition to being distributed to appropriately designated company officials.

Each involved worker will receive a letter describing the incident but deleting any personal or individual comments. A personalized letter describing the individual findings/results will accompany this generalized summary. A copy of the personal letter will be filed in the continuing medical file maintained by WorkCare.

**FIGURE 2-2 (continued)
WORKCARE
POTENTIAL EXPOSURE REPORT**

Name: _____ Date of Exposure: _____

Social Security No.: _____ Age: _____ Sex: _____

Client Contact: _____ Phone No.: _____

Company Name: _____

I. Exposing Agent

Name of Product or Chemicals (if known): _____

Characteristics (if the name is not known)

Solid Liquid Gas Fume Mist Vapor

II. Dose Determinants

What was individual doing? _____

How long did individual work in area before signs/symptoms developed? _____

Was protective gear being used? If yes, what was the PPE? _____

Was their skin contact? _____

Was the exposing agent inhaled? _____

Were other persons exposed? If yes, did they experience symptoms? _____

III. Signs and Symptoms (check off appropriate symptoms)

Immediately With Exposure:

Burning of eyes, nose, or throat
Tearing
Headache
Cough
Shortness of Breath

Chest Tightness / Pressure
Nausea / Vomiting
Dizziness
Weakness

Delayed Symptoms:

Weakness
Nausea / Vomiting
Shortness of Breath
Cough

Loss of Appetite
Abdominal Pain
Headache
Numbness / Tingling

IV. Present Status of Symptoms (check off appropriate symptoms)

Burning of eyes, nose, or throat
Tearing
Headache
Cough
Shortness of Breath
Chest Tightness / Pressure
Cyanosis

Nausea / Vomiting
Dizziness
Weakness
Loss of Appetite
Abdominal Pain
Numbness / Tingling

Have symptoms: (please check off appropriate response and give duration of symptoms)

Improved: _____ Worsened: _____ Remained Unchanged: _____

V. Treatment of Symptoms (check off appropriate response)

None: _____ Self-Medicating: _____ Physician Treated: _____

3.0 SITE BACKGROUND

NAS Pensacola is located in Escambia County, in Florida's northwest coastal area, approximately 5 miles west of the Pensacola City limits. The 950-acre installation was constructed in the early 1940's. Prior to construction, the facility was undeveloped and sparsely vegetated. Land use at NAS Pensacola consists of various military housing, training, and support facilities as well as large industrial complexes for major repairs and refurbishment of aircraft engines and frames. Additional details on the NAS Pensacola facility may be found in the facility administrative record.

3.1 SITE DESCRIPTION

The Tank Farm is a 1.5 acre fenced-in area containing two cut-and-cover storage tanks (Tanks 681 and 682 with capacities of 1.102 million gallons each) and associated pump houses and underground distribution piping. The tanks were installed in December 1943 to store diesel fuel, however, "Bunker C" and Aviation Gasoline (AVGAS) have also been stored at the site. The tanks are not in service and have been abandoned in place. Each tank is 102.5 feet in diameter and 21 feet in depth.

A Closure Assessment (CA) of the site was performed in April 1995. The results of the CA indicated concentrations of petroleum constituents detected in a sample from on-site monitoring wells in excess of Florida Department of Environmental Regulation (FDER), presently the Florida Department of Environmental Protection (FDEP) groundwater standards. In July 1995, a release of an unknown quantity of petroleum constituents was reported to the FDEP based on the detection of these petroleum constituents.

4.0 SCOPE OF WORK

The following is a list of activities that are covered in this HASP for the contamination assessment to be conducted under CTO 0198:

- Mobilization/demobilization
- Soil boring activities (Direct Push Technology or DPT)
- Monitoring well installation, purging, and development
- Multi-media sampling, including:
 - Soils (surface and subsurface)
 - Groundwater (including Natural Attenuation)
 - Investigative-Derived Waste (IDW)
- Decontamination of sampling and heavy equipment
- IDW management

For more detailed description of the associated tasks, refer to the Work Plan (WP) , Statement of Work (SOW#216 and/or Sampling and Analysis Plan (SAP). Any tasks to be conducted outside of the elements listed here will be considered a change in scope requiring modification of this document. The TOM or a designated representative will submit all requested modifications to this document to the HSM.

5.0 TASKS/HAZARDS/ASSOCIATED CONTROL MEASURES SUMMARIZATION

Table 5-1 of this section serves as the primary portion of the site-specific HASP which identifies the tasks that are to be performed as part of the scope of work. This table will be modified and incorporated into this document as new or additional tasks are performed at the site. The anticipated hazards, recommended control measures, air-monitoring recommendations, required Personal Protective Equipment (PPE), and decontamination measures for each site task are discussed in detail. This table and the associated control measures shall be changed, if the scope of work, contaminants of concern, or other conditions change.

Through using the table, site personnel can determine which hazards are associated with each task and at each site and what associated control measures are necessary to minimize potential exposure or injuries related to those hazards. The table also assists field team members in determining which PPE and decontamination procedures to use based on proper air monitoring techniques and site-specific conditions.

As discussed earlier, the Health and Safety Guidance Manual supports this table and HASP. The manual is designed to further explain supporting programs and elements for other site-specific aspects as required by regulatory requirements. The Guidance Manual should be referenced for additional information regarding air monitoring instrumentation, decontamination activities, emergency response, hazard assessments, hazard communication and hearing conservation programs, medical surveillance, PPE, respiratory protection, site control measures, standard work practices, and training requirements. Many of TtNUS' SOPs are also provided in this Guidance Manual.

Safe Work Permits issued for all exclusion zone activities (See Section 9.4 and Attachment IV) will use elements defined in Table 5-1 as the primary reference. The FOL and/or the SSO completing the Safe Work Permit will add additional site-specific information. In situations where the Safe Work Permit is more conservative than the direction provided in Table 5-1, the Safe Work Permit will be followed. As the project develops and more information is gained regarding the contents of buried drums, the SSO will modify the Safe Work Permits to reflect this information.

**TABLE 5-1
TASKS/HAZARDS/CONTROL MEASURES COMPENDIUM FOR
NAVAL AIR STATION – PENSACOLA, PENSACOLA, FLORIDA**

Revision R-1
07/09/01

Tasks/Operation/ Locations	Anticipated Hazards	Recommended Control Measures	Hazard Monitoring	Personal Protective Equipment	Decontamination Procedures
<p>Soil borings using Direct-Push Technology (DPT, such as the Geoprobe®).</p> <p>This task also includes monitoring well installation, development, and purging.</p>	<p><i>Chemical Hazards</i></p> <p>1) Primary types of contaminants include VOCs (primarily Aviation Gasoline [AVGAS]) and SVOCs (diesel fuel and waste oils, including general PAHs). Note that these contaminants may be bound to particulates (dusts, soils, etc.) and contact should be avoided whenever possible. None of the site contaminants, however, are anticipated to be present in significant concentrations to present an inhalation hazard. See Table 6-1 for more information on the chemicals of concern.</p> <p>2) Transfer of contamination into clean areas or onto persons</p> <p><i>Physical hazards</i></p> <p>3) Heavy equipment hazards (pinch/compression points, rotating equipment, hydraulic lines, etc.)</p> <p>4) Noise in excess of 85 dBA</p> <p>5) Energized systems (contact with underground or overhead utilities)</p> <p>6) Lifting (strain/muscle pulls)</p> <p>7) Slip, trips, and falls</p> <p>8) Vehicular and foot traffic</p> <p>9) Ambient temperature extremes (heat stress)</p> <p><i>Natural hazards</i></p> <p>10) Insect/animal bites and stings</p> <p>11) Inclement weather</p>	<p>1) Use real-time monitoring instrumentation, action levels, and identified PPE to control exposures to potentially contaminated media (air, water, soils, etc.). Generation of dusts should be minimized. If airborne dusts are observed, area wetting methods may be used. If area wetting methods are not feasible, termination of activities may be used to minimize exposure to excessive airborne dusts.</p> <p>2) Decontaminate all equipment and supplies between boreholes and prior to leaving the site.</p> <p>3) All equipment to be used will be</p> <ul style="list-style-type: none"> - Inspected in accordance with Federal safety and transportation guidelines, OSHA (1926.600,.601,.602), and manufacturers design and documented as such using Equipment Inspection Sheet (see Attachment III of this HASP). - Operated by knowledgeable operators and ground crew. - Repaired using only manufacturer approved parts and equipment. <p>In addition to the equipment considerations, the following standard operating procedures will be employed:</p> <ul style="list-style-type: none"> - All personnel not directly supporting the direct push operation will remain at least 25 feet from the point of operation. - All loose clothing/protective equipment will be secured to avoid possible entanglement. - Hand signals will be established prior to the commencement of direct push activities. - A remote sampling device must be used to sample drill cuttings near rotating tools. - Work areas will be kept clear of clutter. - All personnel will be instructed in the location and operations of the emergency shut off device(s). This device will be tested initially (and then periodically) to insure its operational status. - Areas will be inspected prior to the movement of direct push rigs and support vehicles to eliminate any physical hazards. This will be the responsibility of the FOL and/or SSO. <p>4) Hearing protection will be used during all subsurface activities.</p> <p>5) All utility clearances must be obtained, in writing, prior to subsurface activities (contact Ron Joyner). Prior to any subsurface investigations, the locations of all underground utilities must be identified and marked.</p> <p>6) Use machinery or multiple personnel for heavy lifts. Use proper lifting techniques.</p> <p>7) Preview work locations for unstable/uneven terrain.</p> <p>8) Traffic and equipment considerations are to include the following:</p> <ul style="list-style-type: none"> - Establish safe zones of approach (i.e. Boom + 3 feet). - Secure all loose articles to avoid possible entanglement. - All equipment shall be equipped with movement warning systems. - All activities are to be conducted consistent with the Base requirements. <p>9) Wear appropriate clothing for weather conditions. Provide acceptable shelter and liquids for field crews. Additional information regarding heat stress concerns is provided in Attachment V and Section 4 of the TINUS Health and Safety Guidance Manual.</p> <p>10) Avoid nesting areas, use repellents. Wear appropriate clothing. Report potential hazards to the SSO. Follow guidance presented in Attachment II of this HASP.</p> <p>11) Suspend or terminate operations until directed otherwise by SSO.</p>	<p>It is not anticipated that potential contaminant concentrations at outdoor sample locations will present an inhalation hazard.</p> <p>A direct reading Photoionization Detector (PID) with a 10.6 eV lamp or higher, or a Flameionization Detector (FID), will be used to screen samples and to detect the presence of any potential volatile organics. Source monitoring of the borehole will be conducted at regular intervals to be determined by the SSO. Positive sustained results at a source or downwind location(s) which may impact operations crew will require the following actions:</p> <ul style="list-style-type: none"> - Monitor the breathing zone of at-risk and downwind employees. Any sustained readings (greater than 1 minute in duration) above daily-established background levels in the breathing zone areas of the at-risk employees requires site activities to be suspended and site personnel to retreat to an unaffected area. - Work may only resume if airborne readings in worker breathing zone areas return to below daily-established background levels. If elevated readings in worker breathing zone persist, the PHSO and HSM will be contacted to determine necessary actions and levels of protection. <p>Site contaminants may adhere to or be part of airborne dusts or particulates generated during site activities. Generation of dusts should be minimized to avoid inhalation of contaminated dusts or particulates. Evaluation of dust concentrations will be performed by observing work conditions for visible dust clouds. Potential exposure to contaminated dust will be controlled using water suppression, by avoiding dust plumes, or evacuating the operation area until dust subsides.</p> <p>Where the utility clearance cannot be determined, subsurface activities shall proceed with extreme caution using hand digging to at least below the frost-line depth (no less than 4 ft. BGS). Also, a magnetometer must be used for periodic down-hole surveys every 2 feet to a depth of at least 10 feet.</p>	<p>All subsurface operations are to be initiated in Level D protection. Level D protection constitutes the following minimum protection</p> <ul style="list-style-type: none"> - Standard field attire (Sleeved shirt; long pants) - Safety shoes (Steel toe/shank) - Safety glasses - Hardhat - Reflective vest for traffic areas - <i>Tyvek coveralls and disposable boot covers if surface contamination is present or if the potential exists for soiling work attire.</i> - <i>Nitrile gloves or leather gloves with surgical style inner gloves</i> - Hearing protection during soil boring activities <i>and for other high noise areas as directed by the SSO.</i> <p><i>(Items in italics are deemed optional as conditions or the FOL or SSO dictate.)</i></p> <p>Note: The Safe Work Permit(s) for this task (see Attachment IV) will be issued at the beginning of each day to address the tasks planned for that day. As part of this task, additional PPE may be assigned to reflect site-specific conditions or special considerations or conditions associated with any identified task.</p>	<p>Personnel Decontamination - Will consist of a soap/water wash and rinse for reusable protective equipment (e.g., gloves). This function will take place at an area adjacent to the drilling operations bordering the support zone.</p> <p>This decontamination procedure for Level D protection will consist of</p> <ul style="list-style-type: none"> - Equipment drop - Soap/water wash and rinse of reusable outer gloves, as applicable - Outer coveralls, boot covers, and/or outer glove removal - Removal, segregation, and disposal of non-reusable PPE in bags/containers provided - Wash hands and face, leave contamination reduction zone.

**TABLE 5-1
TASKS/HAZARDS/CONTROL MEASURES COMPENDIUM FOR
NAVAL AIR STATION – PENSACOLA, PENSACOLA, FLORIDA**

Revision R-1
07/09/01

Tasks/Operation/ Locations	Anticipated Hazards	Recommended Control Measures	Hazard Monitoring	Personal Protective Equipment	Decontamination Procedures
<p>Multi-media sampling, including soil, groundwater (including natural attenuation), and IDW sampling.</p>	<p><i>Chemical Hazards</i></p> <p>1) Primary types of contaminants include VOCs (primarily Aviation Gasoline [AVGAS]) and SVOCs (diesel fuel and waste oils, including general PAHs). Note that these contaminants may be bound to particulates (dusts, soils, etc.) and contact should be avoided whenever possible. None of the site contaminants, however, are anticipated to be present in significant concentrations to present an inhalation hazard. See Table 6-1 for more information on the chemicals of concern.</p> <p>2) Transfer of contamination into clean areas</p> <p><i>Physical hazards</i></p> <p>3) Noise in excess of 85 dBA 4) Lifting (strain/muscle pulls) 5) Pinches and compressions 6) Slip, trips, and falls 7) Ambient temperature extremes (heat stress) 8) Vehicular and foot traffic</p> <p><i>Natural hazards</i></p> <p>9) Insect/animal bites and stings</p> <p>10) Inclement weather</p>	<p>1) Use real-time monitoring instrumentation, action levels, and identified PPE to control exposures to potentially contaminated media (air, water, soils, etc.). Generation of dusts should be minimized. If airborne dusts are observed, area wetting methods may be used. If area wetting methods are not feasible, termination of activities may be used to minimize exposure to observed airborne dusts.</p> <p>2) Decontaminate all equipment and supplies between sampling locations and prior to leaving the site.</p> <p>3) When sampling at the Geoprobe use hearing protection. The use of hearing protection outside of 25 feet from the Geoprobe should be incorporated under the following condition:</p> <p align="center">If you have to raise your voice to talk to someone who is within 2 feet of your location, hearing protection must be worn.</p> <p>4) Use machinery or multiple personnel for heavy lifts. Use proper lifting techniques.</p> <p>5) Keep any machine guarding in place. Avoid moving parts. Use tools or equipment where necessary to avoid contacting pinch points.</p> <p>- A remote sampling device must be used to sample drill cuttings near rotating tools. The equipment operator shall shutdown machinery if the sampler is near moving machinery parts.</p> <p>6) Preview work locations for unstable/uneven terrain.</p> <p>7) Wear appropriate clothing for weather conditions. Provide acceptable shelter and liquids for field crews. Additional information regarding cold/heat stress concerns is provided in Attachment V and Section 4 of the TiNUS Health and Safety Guidance Manual.</p> <p>8) Traffic and equipment considerations are to include the following:</p> <ul style="list-style-type: none"> - Establish safe zones of approach (i.e. Boom + 3 feet). - Secure all loose articles to avoid possible entanglement. - All equipment shall be equipped with movement warning systems. - All activities are to be conducted consistent with the Base requirements. <p>9) Avoid nesting areas, use repellents. Report potential hazards to the SSO. Follow guidance presented in Attachment II of this HASP.</p> <p>10) Suspend or terminate operations until directed otherwise by the SSO.</p>	<p>It is not anticipated that potential contaminant concentrations at outdoor sample locations will present an inhalation hazard.</p> <p>A direct reading Photoionization Detector (PID) with a 10.6 eV lamp or higher, or a Flameionization Detector (FID), will be used to screen samples and to detect the presence of any potential volatile organics. Source monitoring of the borehole will be conducted at regular intervals to be determined by the SSO. Positive sustained results at a source or downwind location(s) which may impact operations crew will require the following actions:</p> <ul style="list-style-type: none"> - Monitor the breathing zone of at-risk and downwind employees. Any sustained readings (greater than 1 minute in duration) above daily-established background levels in the breathing zone areas of the at-risk employees requires site activities to be suspended and site personnel to retreat to an unaffected area. - Work may only resume if airborne readings in worker breathing zone areas return to below daily-established background levels. If elevated readings in worker breathing zone persist, the PHSO and HSM will be contacted to determine necessary actions and levels of protection. <p>Site contaminants may adhere to or be part of airborne dusts or particulates generated during site activities. Generation of dusts should be minimized to avoid inhalation of contaminated dusts or particulates. Evaluation of dust concentrations will be performed by observing work conditions for visible dust clouds. Potential exposure to contaminated dust will be controlled using water suppression, by avoiding dust plumes, or evacuating the operation area until dust subsides.</p>	<p>Level D protection will be utilized for the initiation of all sampling activities.</p> <p>Level D - (Minimum Requirements)</p> <ul style="list-style-type: none"> - Standard field attire (Sleeved shirt; long pants) - Safety shoes (steel toe/shank) - Safety glasses - Surgical style gloves (double-layered if necessary) - Reflective vest for high traffic areas - <i>Hardhat (when overhead hazards exists, or identified as a operation requirement)</i> - <i>Tyvek coveralls and disposable boot covers if surface contamination is present or if the potential for soiling work attire exists.</i> - <i>Hearing protection for high noise areas, or as directed on an operation by operation scenario.</i> <p><i>(Items in italics are deemed optional as conditions or the FOL or SSO dictate.)</i></p> <p>Note: The Safe Work Permit(s) for this task (see Attachment IV) will be issued at the beginning of each day to address the tasks planned for that day. As part of this task, additional PPE may be assigned to reflect site-specific conditions or special considerations or conditions associated with any identified task.</p>	<p>Personnel Decontamination will consist of a removal and disposal of non-reusable PPE (gloves, coveralls, etc., as applicable). The decon function will take place at an area adjacent to the site activities. This procedure will consist of:</p> <ul style="list-style-type: none"> - Equipment drop - Outer coveralls, boot covers, and/or outer glove removal (as applicable) - Removal, segregation, and disposal of non-reusable PPE in bags/containers provided - Soap/water wash and rinse of reusable PPE (e.g., hardhat) if potentially contaminated - Wash hands and face, leave contamination reduction zone.

**TABLE 5-1
TASKS/HAZARDS/CONTROL MEASURES COMPENDIUM FOR
NAVAL AIR STATION – PENSACOLA, PENSACOLA, FLORIDA**

Revision R-1
07/09/01

Tasks/Operation/ Locations	Anticipated Hazards	Recommended Control Measures	Hazard Monitoring	Personal Protective Equipment	Decontamination Procedures
Mobilization/ Demobilization	<p><i>Physical Hazards</i></p> <ol style="list-style-type: none"> 1) Lifting (strain/muscle pulls) 2) Pinches and compressions 3) Slip, trips, and falls 4) Heavy equipment hazards (rotating equipment, hydraulic lines, etc.) 5) Vehicular and foot traffic 6) Ambient temperature extremes (heat stress) <p><i>Natural hazards</i></p> <ol style="list-style-type: none"> 7) Insect/animal bites and stings 	<ol style="list-style-type: none"> 1) Use machinery or multiple personnel for heavy lifts. Use proper lifting techniques. 2) Keep any machine guarding in place. Avoid moving parts. Use tools or equipment where necessary to avoid contacting pinch points. 3) Preview work locations for unstable/uneven terrain. 4) All equipment will be <ul style="list-style-type: none"> - Inspected in accordance with OSHA, and manufacturer's design. - Operated by knowledgeable operators, and knowledgeable ground crew. 5) Traffic and equipment considerations are to include the following: <ul style="list-style-type: none"> - Establish safe zones of approach (i.e. Boom + 3 feet). - Secure all loose articles to avoid possible entanglement. - All equipment shall be equipped with movement warning systems. - All activities are to be conducted consistent with the Base requirements. 6) Wear appropriate clothing for weather conditions. Provide acceptable shelter and liquids for field crews. Additional information regarding cold/heat stress concerns is provided in Section 4 of the TtNUS Health and Safety Guidance Manual. 7) Avoid nesting areas, use repellents. Report potential hazards to the SSO. Follow guidance presented in Attachment II of this HASP. 	Not required	<p>Level D - (Minimum Requirements)</p> <ul style="list-style-type: none"> - Standard field attire (Sleeved shirt; long pants) - Safety shoes (Steel toe/shank) - Safety glasses - Hardhat (when overhead hazards exists, or identified as a operation requirement) - Reflective vest for high traffic areas - Hearing protection for high noise areas, or as directed on an operation by operation scenario. <p><i>(Items in italics are deemed optional as conditions or the FOL or SSO dictate.)</i></p>	Not required
Decontamination of Sampling and Heavy Equipment	<p><i>Chemical Hazards</i></p> <ol style="list-style-type: none"> 1) Primary types of contaminants include VOCs (primarily Aviation Gasoline [AVGAS]) and SVOCs (diesel fuel and waste oils, including general PAHs). Note that these contaminants may be bound to particulates (dusts, soils, etc.) and contact should be avoided whenever possible. None of the site contaminants, however, are anticipated to be present in significant concentrations to present an inhalation hazard. See Table 6-1 for more information on the chemicals of concern. 2) Decontamination fluids - Liquinox (detergent), acetone or isopropanol <p><i>Physical Hazards</i></p> <ol style="list-style-type: none"> 3) Lifting (strain/muscle pulls) 4) Noise in excess of 85 dBA 5) Flying projectiles 6) Vehicular and foot traffic 7) Ambient temperature extremes (heat stress) 8) Slips, trips, and falls <p><i>Natural Hazards</i></p> <ol style="list-style-type: none"> 9) Inclement weather 	<ol style="list-style-type: none"> 1) and 2) Employ protective equipment to minimize contact with site contaminants and hazardous decontamination fluids. Obtain manufacturer's MSDS for any decontamination fluids used onsite. These must be used in well-ventilated areas, such as outdoors. Use appropriate PPE as identified on MSDS. All chemicals used must be listed on the Chemical Inventory for the site, and site activities must be consistent with the Hazard Communication section of the Health and Safety Guidance Manual (Section 5). 3) Use multiple persons where necessary for lifting and handling sampling equipment for decontamination purposes. 4) Wear hearing protection when operating pressure washer. 5) Use eye and face protective equipment when operating pressure washer. All other personnel must be restricted from the area. 6) Traffic and equipment considerations are to include the following: <ul style="list-style-type: none"> - Establish safe zones of approach. - All equipment shall be equipped with movement warning systems. - All activities are to be conducted consistent with the Base requirements. 7) Wear appropriate clothing for weather conditions. Provide acceptable shelter and liquids for field crews. Additional information regarding cold/heat stress concerns is provided in Attachment V and Section 4 of the TtNUS Health and Safety Guidance Manual. 8) Preview work locations for unstable/uneven terrain. 9) Suspend or terminate operations until directed otherwise by SSO. 	Use visual observation, and real-time monitoring instrumentation to ensure all equipment has been properly cleaned of contamination and dried. After decon is completed, screen equipment with a PID/FID. If any elevated readings (i.e., above background) are observed, perform decon again and rescreen. Repeat until no elevated PID/FID readings are noted.	<p>For Heavy Equipment This applies to high pressure soap/water, steam cleaning wash and rinse procedures.</p> <p>Level D Minimum requirements -</p> <ul style="list-style-type: none"> - Standard field attire (Long sleeve shirt; long pants) - Safety shoes (Steel toe/shank) - Chemical resistant boot covers - Nitrile outer gloves - PVC Rainsuits or PE or PVC coated Tyvek - Safety glasses underneath a splash shield - Hearing protection (plugs or muffs) <p><i>Items in italics are at the discretion of the SSO.</i></p> <p>For sampling equipment (trowels, MacroCore Samplers, bailers, etc.), the following PPE is required</p> <p>Note: Consult MSDS for PPE guidance. Otherwise, observe the following.</p> <p>Level D Minimum requirements -</p> <ul style="list-style-type: none"> - Standard field attire (Long sleeve shirt; long pants) - Safety shoes (Steel toe/shank) - Nitrile outer gloves - Safety glasses <p>In the event of overspray of chemical decontamination fluids employ PVC Rainsuits or PE or PVC coated Tyvek as necessary.</p>	<p>Personnel Decontamination will consist of a soap/water wash and rinse for reusable outer protective equipment (boots, gloves, PVC splash suits, as applicable). The decon function will take place at an area adjacent to the site activities. This procedure will consist of:</p> <ul style="list-style-type: none"> - Equipment drop - Soap/water wash and rinse of outer boots and gloves, as applicable - Soap/water wash and rinse of the outer splash suit, as applicable - Disposable PPE will be removed and bagged. <p>Equipment Decontamination - All heavy equipment decontamination will take place at a centralized decontamination pad utilizing steam or pressure washers. Heavy equipment will have the wheels and tires cleaned along with any loose debris removed, prior to transporting to the central decontamination area. All site vehicles will have restricted access to exclusion zones, and have their wheels/tires sprayed off as not to track mud onto the roadways servicing this installation. Roadways shall be cleared of any debris resulting from the onsite activity.</p> <p>Sampling Equipment Decontamination</p> <p>Sampling equipment will be decontaminated as per the requirements in the Sampling and Analysis Plan and/or Work Plan.</p> <p>MSDS for any decon solutions (Alconox, isopropanol, etc.) will be obtained and used to determine proper handling / disposal methods and protective measures (PPE, first-aid, etc.).</p> <p>All equipment used in the exclusion zone will require a complete decontamination between locations and prior to removal from the site.</p> <p>The FOL or the SSO will be responsible for evaluating equipment arriving onsite and leaving the site. No equipment will be authorized access or exit without this evaluation.</p>

**TABLE 5-1
TASKS/HAZARDS/CONTROL MEASURES COMPENDIUM FOR
NAVAL AIR STATION – PENSACOLA, PENSACOLA, FLORIDA**

Revision R-1
07/09/01

Tasks/Operation/ Locations	Anticipated Hazards	Recommended Control Measures	Hazard Monitoring	Personal Protective Equipment	Decontamination Procedures
IDW management and moving IDW drums to storage areas	<p><i>Chemical Hazards</i></p> <p>1) Primary types of contaminants include VOCs (primarily Aviation Gasoline [AVGAS]) and SVOCs (diesel fuel and waste oils, including general PAHs). Note that these contaminants may be bound to particulates (dusts, soils, etc.) and contact should be avoided whenever possible. None of the site contaminants, however, are anticipated to be present in significant concentrations to present an inhalation hazard. See Table 6-1 for more information on the chemicals of concern.</p> <p>2) Transfer of contamination into clean areas</p> <p><i>Physical hazards</i></p> <p>3) Noise in excess of 85 dBA 4) Lifting (strain/muscle pulls) 5) Pinches and compressions 6) Slip, trips, and falls 7) Vehicular and foot traffic 8) Ambient temperature extremes (heat stress)</p> <p><i>Natural hazards</i></p> <p>9) Insect/animal bites and stings</p>	<p>1) Employ real-time monitoring instrumentation, action levels, and identify PPE to control exposures to potentially contaminated media (e.g. air, water, soils).</p> <p>2) Decontaminate all equipment and supplies, if they become contaminated, between locations and prior to leaving the site.</p> <p>3) When working near heavy equipment, use hearing protection.</p> <p>4) Use machinery or multiple personnel for heavy lifts. Use proper lifting techniques.</p> <p>5) Keep any machine guarding in place. Avoid moving parts. Use tools or equipment where necessary to avoid contacting pinch points.</p> <p>6) Preview work locations for unstable/uneven terrain.</p> <p>7) Traffic and equipment considerations are to include the following: - Establish safe zones of approach (i.e. Boom + 3 feet). - Secure all loose articles to avoid possible entanglement. - All equipment shall be equipped with movement warning systems. - All activities are to be conducted consistent with the Base requirements.</p> <p>8) Wear appropriate clothing for weather conditions. Provide acceptable shelter and liquids for field crews. Additional information regarding cold/heat stress concerns is provided in Section 4 of the TtNUS Health and Safety Guidance Manual.</p> <p>9) Avoid nesting areas, use repellents. Report potential hazards to the SSO. Follow guidance presented in Attachment II of this HASP.</p>	<p>It is not anticipated that potential contaminant concentrations at outdoor sample locations will present an inhalation hazard.</p> <p>A direct reading Photoionization Detector (PID) with a 10.6 eV lamp or higher, or a Flameionization Detector (FID), will be used to screen samples and to detect the presence of any potential volatile organics. Source monitoring of the borehole will be conducted at regular intervals to be determined by the SSO. Positive sustained results at a source or downwind location(s) which may impact operations crew will require the following actions:</p> <ul style="list-style-type: none"> - Monitor the breathing zone of at-risk and downwind employees. Any sustained readings (greater than 1 minute in duration) above daily-established background levels in the breathing zone areas of the at-risk employees requires site activities to be suspended and site personnel to retreat to an unaffected area. - Work may only resume if airborne readings in worker breathing zone areas return to below daily-established background levels. If elevated readings in worker breathing zone persist, the PHSO and HSM will be contacted to determine necessary actions and levels of protection. <p>Site contaminants may adhere to or be part of airborne dusts or particulates generated during site activities. Generation of dusts should be minimized to avoid inhalation of contaminated dusts or particulates. Evaluation of dust concentrations will be performed by observing work conditions for visible dust clouds. Potential exposure to contaminated dust will be controlled using water suppression, by avoiding dust plumes, or evacuating the operation area until dust subsides.</p>	<p>Level D protection will be utilized for the initiation of all sampling activities.</p> <p>Level D - (Minimum Requirements)</p> <ul style="list-style-type: none"> - Standard field attire (long sleeve shirt; long pants) - Nitrile or cotton/leather work gloves with surgical style inner gloves - Safety shoes (steel toe/shank) - Safety glasses - <i>Hardhat (when overhead hazards exists, or identified as a operation requirement)</i> - <i>Reflective vest for high traffic areas</i> - <i>Tyvek coveralls and disposable boot covers if surface contamination is present or if the potential for soiling work attire exists.</i> - <i>Hearing protection for high noise areas, or as directed on an operation by operation scenario.</i> <p><i>(Items in italics are deemed optional as conditions or the FOL or SSO dictate.)</i></p>	<p>Personnel Decontamination will consist of a soap/water wash and rinse for reusable outer protective equipment (boots, gloves, PVC splash suits, as applicable). The decon function will take place at an area adjacent to the site activities. This procedure will consist of:</p> <ul style="list-style-type: none"> - Equipment drop - Soap/water wash and rinse of outer boots and gloves, as applicable - Soap/water wash and rinse of the outer splash suit, as applicable - Disposable PPE will be removed and bagged.

6.0 HAZARD ASSESSMENT

The following section provides information regarding the chemical, physical, and natural hazards anticipated to be present during the activities to be conducted. Table 6-1 provides information related to chemical constituents that have been identified by analysis or are suspected to be present at the site based on historical data. Specifically, toxicological information, exposure limits, symptoms of exposure, physical properties, and air monitoring and sampling data are discussed in the table.

6.1 CHEMICAL HAZARDS

The potential health hazards associated with the Fuel Farm include inhalation, ingestion, and dermal contact of various contaminants that may be present in shallow and deep soils and groundwater. As the focus of this contamination assessment is to conduct additional sampling of various media at the site, concentrations of the chemical hazards potentially present are not fully determined. Based on prior activities at the site and limited prior sampling; however, the types of contaminants anticipated include AVGAS, diesel fuel, and waste oil products. The following have been identified as the primary classes of hazards for these contaminants:

- Volatile Organic Compounds (VOCs), primarily Aviation Gasoline (AVGAS)
- Semi-Volatile Organic Compounds (SVOCs), primarily diesel fuel and waste oils, including general Polynuclear Aromatic Hydrocarbons (PAHs).

Table 6-1 provides information on the individual substances likely to be present at the sites of concern. Included is information on the toxicological, chemical, and physical properties of these substances. It is anticipated that the greatest potential for exposure to site contaminants is during intrusive activities (drilling, soil sampling, etc.). Exposure to these compounds is most likely to occur through ingestion and inhalation of contaminated soil or water, or hand-to-mouth contact during soil disturbance activities. For this reason, PPE and basic hygiene practices (washing face and hands before leaving site) will be extremely important. Inhalation exposure will be avoided by using appropriate PPE and engineering controls where necessary.

6.2 PHYSICAL HAZARDS

The physical hazards that may be present during the performance of site activities are summarized below:

- Heavy equipment hazards (pinch/compression points, rotating equipment, etc.).
- Slips, trips, and falls

- Energized systems (contact with underground or overhead utilities)
- Lifting (strain/muscle pulls)
- Noise in excess of 85 decibels (dBA)
- Inclement weather
- Flying projectiles
- Ambient temperature extremes (heat stress)
- Pinches and compressions
- Vehicular and foot traffic

These physical hazards are discussed in Table 5-1 as applicable to each site task. Further, many of these hazards are discussed in detail in Section 4.0 of the Health and Safety Guidance Manual. Specific discussions on some of these hazards are presented below.

6.2.1 Heavy Equipment Hazards (Pinch/compression points, rotating equipment, etc.)

Often the hazards associated with drilling operations are the most dangerous to be encountered during site activities. The SSO will thoroughly discuss safe drilling procedures during the pre-activities training session. All site personnel will sign the form in Figure 8-2 documenting that they received the training and understand the procedures. The following rules will apply to all drilling operations:

- Each rig must be equipped with emergency stop devices which will be tested daily to ensure that they are operational.
- Long handled shovels or equivalent shall be used to clear cuttings from the borehole and rotating equipment.
- The driller may not leave the controls when the augers are rotating.

6.2.2 Energized Systems (Contact with Underground or Overhead Utilities)

Underground utilities such as pressurized lines, water lines, telephone lines, buried utility lines, and high voltage power lines are known to be present throughout the facility. Clearance of underground and overhead utilities for each sample location will be coordinated with NAS Pensacola personnel. Byas Glover is the point-of-contact for utilities clearance and can be reached at (850) 820-5651. Additionally, drilling operations will be conducted at a safe distance (>20 feet) from overhead power lines. Whenever underground utilities are suspected to be close to subsurface sampling locations, the borehole will be advanced to a minimum of five (5) feet with a hand auger prior to drilling. As built drawings may also be utilized for additional clarification. In

certain cases, Base personnel may need to de-energize electrical cables using facility lockout/tagout procedures to insure electrical hazards are eliminated.

6.2.3 Ambient Temperature Extremes

Overexposure to high ambient temperatures (heat stress) may exist during performance of this work depending on the project schedule. Extremely cold temperatures are not expected to be encountered due to project location. Work performed when ambient temperatures exceed 70°F may result in varying levels of heat stress (heat rash, heat cramps, heat exhaustion, and/or heat stroke) depending on variables such as wind speed, humidity, and percent sunshine, as well as physiological factors such as metabolic rate and skin moisture content. Additionally, workload and level of protective equipment will affect the degree of exposure. Site personnel will be encouraged to drink plenty of fluids to replace those lost through perspiration. Additional information such as Work-Rest Regimens and personnel monitoring may be found in Attachment V and Section 4.0 of the Guidance Manual. The SSO will recommend additional heat stress control measures as they are deemed necessary as per ACGIH guidelines.

6.3 NATURAL HAZARDS

Insect/animal bites and stings, poisonous plants, and inclement weather are natural hazards that may be present given the location of activities to be conducted. In general, avoidance of areas of known infestation or growth will be the preferred exposure control for insects/animals and poisonous plants. Specific discussion on principle hazards of concern follows:

6.3.1 Insect/animal Bites and Stings

Various insects and animals may be present and should be considered. For example, fire ants present a unique situation when working outdoors in Florida. Their aggressive behavior and their ability to sting repeatedly can pose a unique health threat. The sting injects venom that causes an extreme burning sensation. Pustules form which can become infected if scratched. Allergic reactions of people sensitive to the venom include dizziness, swelling, shock and in extreme cases unconsciousness and death. People exhibiting such symptoms should see a physician. Fire ants can be identified by their habitat. They build mounds in open sunny areas sometimes supported by a wall or shrub. The mound has no external opening. The size of the mound can range from a few inches across to some which are in excess of two feet or more in height and diameter. When disturbed they defend it by swarming out and over the mound, even running up grass blades and sticks.

Also, areas to be investigated could be prime nesting and/or hiding locations for snakes and other insects. Personnel should avoid reaching into areas that are not visibly clear of snakes or insects. Snake chaps will be worn in areas of known or anticipated snake infestation. All site personnel who are allergic to stinging

insects such as bees, wasps, and hornets must be particularly careful since severe illness and death may result from allergic reactions. As with any medical condition or allergy, information regarding the condition must be listed on the Medical Data Sheet and the FOL and SSO notified.

There are various areas throughout the U.S. where Lyme Disease is endemic. Fortunately, Florida is not one of these areas. Nonetheless, personnel should be aware of the hazards of tick bites and Lyme Disease. The longer a disease carrying tick remains attached to the body, the greater the potential for contracting the disease. Wearing long sleeved shirts and long pants (tucked into boots). As well as performing frequent body checks will prevent long term attachment. Site first aid kits should be equipped with medical forceps and rubbing alcohol to assist in tick removal. For information regarding tick removal procedures, and symptoms of exposure consult Attachment II of this HASP or Section 4.0 of the Health and Safety Guidance Manual.

An Office of Natural Resources or similar entity on Base should be contacted for further direction on the hazards and precautions of naturally occurring wildlife and insects.

6.3.2 Inclement Weather

Project tasks under this Scope of Work will be performed outdoors and near water. As a result, inclement weather may be encountered. In the event that adverse weather conditions arise (electrical storms, hurricanes, etc.), the FOL and/or the SSO will be responsible for temporarily suspending or terminating activities until hazardous conditions no longer exist.

**TABLE 6-1
CHEMICAL, PHYSICAL, AND TOXICOLOGICAL DATA
NAVAL AIR STATION PENSACOLA
PENSACOLA, FLORIDA**

**Revision 1
7/09/01**

Substance	CAS No.	Air Monitoring/Sampling Information		Exposure Limits	Warning Property Rating	Physical Properties	Health Hazard Information
Diesel Fuel No.2-D	Mixture	Components of this substance will be detected readily; however, no documentation exists as to the relative response ratio of either PID or FID.	Air sampling use charcoal tube as a collection media; carbon disulfide desorption; GC/FID detection. Sampling and analytical protocol in accordance with NIOSH Method #1550.	OSHA; NIOSH; ACGIH; 5 mg/m ³ as mineral oil mist. In addition NIOSH and ACGIH establish 10 mg/m ³ as a STEL.	Kerosene odor Recommended air-purifying cartridges: Organic vapor Recommended gloves: Nitrile	Boiling Pt: <300-550°F; 149-288°C Melting Pt: Not available Solubility: Negligible Flash Pt: 95-145°F; 35-62°C Autoignition: 475°F, 246°C LEL/LFL: 0.6% UEL/UFL: 8.0% Vapor Density: >5 Vapor Pressure: <0.1 mmHg @ 70°F; 21°C Specific Gravity: 0.80 Incompatibilities: strong oxidizers, halogens, and hypochlorites Appearance and odor: Colorless to amber with a kerosene odor	Prolonged or repeated exposures to this product may cause skin and eye irritation. Because of the defatting capabilities, this exposure may lead to a dermatitis condition. High vapor concentrations are irritating to the eyes and respiratory tract. Exposure to high airborne concentrations may result in narcotic effects, including dizziness, headaches, and anesthetic to unconsciousness. High concentrations in a confined space may adequately displace oxygen thereby resulting in suffocation.
Waste Oils All information is based on mineral oil	Mixture N.E. 8012-95-1 for mineral oil	Varies between fractions however waste oils tend to be less volatile. The FID tends to handle the longer chained aliphatic hydrocarbons more efficiently than its PID counterpart and would be selected as the instrument of choice.	Sampling and analytical protocol shall be in accordance with NIOSH Method #5026 (the recommended method for mineral oil mist).	ACGIH; NIOSH: 5 mg/m ³ (oil mists); 10 mg/m ³ STEL. OSHA: 5 mg/m ³ (Oil mists)	Non-volatile substance, therefore no respiratory protection is required. In an aerosol form, dust and mist respirator would be considered acceptable for up to 500 mg/m ³ . Recommended gloves: Any glove suitable to prevent skin contact (Nitrile has been the one most widely used for the other substances, and will be acceptable). Natural rubber gloves should be avoided. Recommended gloves: Nitrile	Boiling Pt: 680°F; 360°C Melting Pt: Not available Solubility: Insoluble Flash Pt: 275-500°F; 135-260°C depends on the distillation fraction LEL/LFL: Not available UEL/UFL: Not available Vapor Density: Not available Vapor Pressure: <0.5 mmHg Specific Gravity: 0.90 Incompatibilities: None reported Appearance and odor: Colorless, oily, with an odor of burned lubricating oil.	Minor irritation to the eyes, skin, and respiratory system.
Aviation Gasoline (AVGAS or gasoline)	8006-61-9	Relative response ratios for the components of gasoline range from 100 - 200% for PID and FID detection.	See components for measurement considerations.	ACGIH & OSHA: 300 ppm 500 ppm STEL NIOSH: Reduce to lowest feasible concentration.	Respiratory Protection: Odor threshold 0.7 ppm, adequate air purifying respirator with organic vapor cartridges up to 100 ppm. Recommended Gloves: Nitrile >6.00 hrs; PV alcohol >6.00 hrs; Viton/neoprene >8.00 hrs	Boiling Pt: 102°F; 39°C Melting Pt: Not available Solubility: Negligible Flash Pt: -50°F; -45°C LEL/LFL: 1.4% UEL/UFL: 7.6% Vapor Density: ~5 Vapor Pressure: 38-300 mmHg (varies seasonally) Specific Gravity: 0.74 @ 20/20°C Incompatibilities: Strong oxidizers, peroxides, strong acids, and perchlorates Appearance and Odor: Colorless liquid with gasoline odor.	Overexposure to this substance may result in irritation to the eyes, skin, and mucous membranes. Systemically, headache, fatigue, blurred vision, dizziness, slurred speech, confusion, possible convulsion, and chemical pneumonia (aspiration). Prolonged or chronic exposures may result in possible liver or kidney damage. Components of this substance have been determined to be confirmed human carcinogens.

TABLE 6-1
CHEMICAL, PHYSICAL, AND TOXICOLOGICAL DATA
 NAVAL AIR STATION PENSACOLA, PENSACOLA, FLORIDA
 PAGE 2

Revision 1
7/09/01

Substance	CAS No.	Air Monitoring/Sampling Information		Exposure Limits	Warning Property Rating	Physical Properties	Health Hazard Information
General PAHs / Coal Tar Pitch Volatiles / Creosote / cresol (Fluoranthene, pyrene, benzo(a)anthracene, benzo(a)pyrene, benzo(f)fluoranthene, benzo(k)fluoranthene), etc.)	(CAS Numbers vary depending on specific compound)	PID: I.P. of 8.97 eV, relative response ratio unknown. FID: Response factor unknown but given the substances flammability, detection by FID can be anticipated.	Refer to NIOSH methods for each specific compound for appropriate air sampling protocols. Many PAHs can be sampled using NIOSH Method 5506 or 5515 - Teflon filter with support ring - High pressure liquid chromatography with UV detector. For cresol (a major constituent of creosote) by silica gel or xad-7 sorbent tube; Acetone desorption and analysis by gas chromatography - flame ionization detector or high-pressure liquid chromatography. (NIOSH Method #2001, or OSHA Method #32)	General PAHs: Most PAHs have no established exposure limits. Other Coal Tar Pitch Volatiles / PAHs such as chrysene and benzo(a)pyrene have an exposure limit of 0.2 mg/m ³ (OSHA and ACGIH). 0.1 mg/m ³ - (NIOSH) Creosote / Cresol: OSHA; ACGIH: 5 ppm NIOSH: 2.3 ppm IDLH: 80 mg/m ³	Adequate - use a full-face air-purifying respirator with organic vapor / dust/mist cartridge up to 250 ppm. Cresol has an Odor Threshold of 0.00005-0.0079 ppm. Recommended gloves: Viton >96.00 hrs; butyl rubber >90.00 hrs; neoprene >4.50 hrs	Properties of various PAHs/Coal Tar Pitch Volatiles vary depending upon the specific compound. <i>For Creosote/Cresol:</i> Boiling Pt: 376-397°F; 191-203°C Melting Pt: 52-96°F; 10.9-35.5°C Solubility: Insoluble Flash Pt: 178°F; 81°C LEL/LFL: Not available UEL/UFL: Not available Vapor Density: 3.72 Vapor Pressure: 1 mmHg @ 100-127°F; 38-53°C Specific Gravity: 1.030-1.038 Incompatibilities: Nitric acid, oleum, chlorosulfonic acid, oxidizers Appearance and Odor: Yellowish or colorless, flammable, oily liquid (often brownish because of impurities or oxidation)	Regulated based on effects on respiratory tract and skin irritation. Other effects may include eye irritation and central nervous system, disturbances. Acute exposures may result in difficulty breathing, respiratory failure and skin and eye irritation and burns. Chronic exposure may damage the liver, kidneys, lungs and skin and cause photosensitivity. IARC, NTP, NIOSH, ACGIH, and the EPA list some PAHs such as benzo(a)pyrene as a potential carcinogen (ARC 2A, NTP-2, ACGIH TLV-A2, NIOSH-X, EPA-B2).

7.0 AIR MONITORING

Direct reading instruments will be used at the site to detect and evaluate the presence of site contaminants and other potentially hazardous conditions. As a result, specific air monitoring measures and requirements are established in Table 5-1 pertaining to the specific hazards and tasks of an identified operation. Additionally, the Health and Safety Guidance Manual, Section 1.0, contains detailed information regarding direct reading instrumentation, as well as general calibration procedures of various instruments.

7.1 INSTRUMENTS AND USE

Instruments will be used primarily to monitor source points and worker breathing zone areas, while observing instrument action levels. Action levels are discussed in Table 5-1 as they may apply to a specific task or location.

7.1.1 Photoionization Detector or Flame Ionization Detector

In order to accurately monitor for any substances which may present an exposure potential to site personnel, a Photoionization Detector (PID) using a lamp energy of 10.6 eV or higher will be used. This instrument will be used to monitor potential source areas and to screen the breathing zones of employees during site activities. The PID has been selected because it is capable of detecting the organic vapors of concern (NOTE: A Flame Ionization Detector [FID] may be used as an alternative to the PID).

Prior to the commencement of any field activities, the background levels of the site must be determined and noted. Daily background readings will be taken away from any areas of potential contamination. These readings, any influencing conditions (i.e., weather, temperature, and humidity) and site location must be documented in the field operations logbook or other site documentation (e.g., sample log sheet).

7.1.2 Hazard Monitoring Frequency

Table 5-1 presents the frequencies that hazard monitoring will be performed as well as the action levels which will initiate the use of elevated levels of protection. The SSO may decide to increase these frequencies based on instrument responses and site observations. The frequency at which monitoring is performed will not be reduced without the prior consent of the PHSO or HSM.

7.2 INSTRUMENT MAINTENANCE AND CALIBRATION

Hazard monitoring instruments will be maintained and pre-field calibrated by the TtNUS Equipment Manager. Operational checks and field calibration will be performed on all instruments each day prior to

their use. Field calibration will be performed on instruments according to manufacturer's recommendations (for example, the PID must be field calibrated daily and an additional field calibration must be performed at the end of each day to determine any significant instrument drift). These operational checks and calibration efforts will be performed in a manner that complies with the employees health and safety training, the manufacturer's recommendations, and with the applicable manufacturer standard operating procedure (copies of which can be found in the Health & Safety Guidance Manual which will be maintained on site for reference). All calibration efforts must be documented. Figure 7-1 is provided for documenting these calibration efforts. This information may instead be recorded in a field operations logbook, provided that all of the information specified in Figure 7-1 is recorded. This required information includes the following:

- Date calibration was performed
- Individual calibrating the instrument
- Instrument name, model, and serial number
- Any relevant instrument settings and resultant readings (before and after) calibration
- Identification of the calibration standard (lot no., source concentration, supplier)

Any relevant comments or remarks

8.0 TRAINING/MEDICAL SURVEILLANCE REQUIREMENTS

8.1 INTRODUCTORY/REFRESHER/SUPERVISORY TRAINING

This section is included to specify health and safety training and medical surveillance requirements for both TtNUS and subcontractor personnel participating in site activities.

8.1.1 Requirements for TtNUS Personnel

All TtNUS personnel must complete 40 hours of introductory hazardous waste site training prior to performing work at the NAS Pensacola facility. Additionally, TtNUS personnel who have had introductory training more than 12 months prior to site work must have completed 8 hours of refresher training in the past 12 months before being cleared for site work. In addition, 8-hour supervisory training in accordance with 29 CFR 1910.120 (e)(4) will be required for site supervisory personnel.

Documentation of TtNUS introductory, supervisory, and refresher training as well as site-specific training will be maintained at the project. Copies of certificates or other official documentation will be used to fulfill this requirement.

8.1.2 Requirements for Subcontractors

All TtNUS subcontractor personnel must have completed introductory hazardous waste site training or equivalent work experience as defined in OSHA Standard 29 CFR 1910.120 (e). Additionally, personnel who have had the introductory training more than 12 months ago, are required to have 8 hours of refresher training meeting the requirements of 29 CFR 1910.120 (e)(8) prior to performing field work at the NAS Pensacola facility if required. TtNUS subcontractors must certify that each employee has had such training by sending TtNUS a letter, on company letterhead, containing the information in the example letter provided as in Figure 8-1 and by providing copies of certificates for all subcontractor personnel participating in site activities.

**FIGURE 8-1
TRAINING LETTER**

The following statements must be typed on company letterhead and signed by an officer of the company and accompanied by copies of personnel training certificates:

LOGO
XYZ CORPORATION
555 E. 5th Street
Nowheresville, Kansas 55555

Month, day, year

Mr. Gerald Walker
Tetra Tech NUS, Inc.
Task Order Manager
1401 Oven Park Drive
Suite 102
Tallahassee, Florida, 32308

Subject: HAZWOPER Training for NAS Pensacola, Pensacola, Florida

Dear Mr. Walker:

As an officer of XYZ Corporation, I hereby state that I am aware of the potential hazardous nature of the subject project. I also understand that it is our responsibility to comply with all applicable occupational safety and health regulations, including those stipulated in Title 29 of the Code of Federal Regulations (CFR), Parts 1900 through 1910 and Part 1926.

I also understand that Title 29 CFR 1910.120, entitled "Hazardous Waste Operations and Emergency Response," requires appropriate level of training for certain employees engaged in hazardous waste operations. In this regard, I hereby state that the following employees have had 40 hours of introductory hazardous waste site training or equivalent work experience as requested by 29 CFR 1910.120(e) and have had 8 hour of refresher training as applicable and as required by 29 CFR 1910.120(e)(8) and that site supervisory personnel have had training in accordance with 29 CFR 1910.120(e)(4).

LIST FULL NAMES OF EMPLOYEES AND THEIR SOCIAL SECURITY NUMBERS HERE.

Should you have any questions, please contact me at (555) 555-5555

Sincerely,

(Name and Title of Company Officer)

Enclosed: Training Certificates

8.2 SITE-SPECIFIC TRAINING

TtNUS will provide site-specific training to all TtNUS employees and subcontractor personnel who will perform work on this project. Site-specific training will also be provided to all personnel (U.S. Department of Defense, EPA, etc.) who may enter the site to perform functions that may or may not be directly related to site operations. Site-Specific training will include:

- Names of designated personnel and alternates responsible for site safety and health
- Safety, health, and other hazards present on site
- Use of personal protective equipment
- Safe use of engineering controls and equipment
- Medical surveillance requirements
- Signs and symptoms of overexposure
- Contents of the Health and Safety Plan
- Emergency response procedures (evacuation and assembly points)
- Incipient response procedures
- Review of the contents of relevant Material Safety Data Sheets

Site-specific documentation will be established through the use of Figure 8-2. All site personnel and visitors must sign this document upon receiving site-specific training.

8.3 MEDICAL SURVEILLANCE

8.3.1 Medical Surveillance Requirements for TtNUS Personnel

All TtNUS personnel participating in project field activities will have had a physical examination meeting the requirements of TtNUS's medical surveillance program and will be medically qualified to perform hazardous waste site work using respiratory protection.

Documentation for medical clearances will be maintained in the TtNUS Jacksonville office and made available, as necessary.

8.3.2 Medical Surveillance Requirements for Subcontractors

Subcontractors are required to obtain a certificate of their ability to perform hazardous waste site work and to wear respiratory protection. The "Subcontractor Medical Approval Form" provided in Figure 8-3 shall be used to satisfy this requirement, providing it is properly completed and signed by a licensed physician.

Subcontractors who have a company medical surveillance program meeting the requirements of paragraph (f) of OSHA 29 CFR 1910.120 can substitute "Subcontractor Medical Approval Form" (See Figure 8-3) with a letter, on company letterhead, containing all of the information in the example letter presented in Figure 8-4 of this HASP.

8.3.3 Requirements for All Field Personnel

Each field team member (including subcontractors) and visitors entering the exclusion zone(s) shall be required to complete and submit a copy of Medical Data Sheet found in the TtNUS Health and Safety Guidance Manual. This shall be provided to the SSO, prior to participating in site activities. The purpose of this document is to provide site personnel and emergency responders with additional information that may be necessary in order to administer medical attention.

8.4 SUBCONTRACTOR EXCEPTIONS

Subcontractors who will not enter the exclusion zone during intrusive operations, and whose activities involve no potential for exposure to site contaminants, will not be required to meet the requirements for training/medical surveillance other than those stated for site-specific training (See Section 8.2).

FIGURE 8-3

SUBCONTRACTOR MEDICAL APPROVAL FORM

For employees of _____
Company Name

Participant Name: _____ Date of Exam: _____

Part A

The above-named individual has:

1. Undergone a physical examination in accordance with OSHA Standard 29 CFR 1910.120, paragraph (f) and found to be medically -

- Qualified to perform work at the NAS Pensacola, work site
- Not qualified to perform work at the NAS Pensacola, work site

And,

2. Undergone a physical examination as per OSHA 29 CFR 1910.134(b)(10) and found to be medically -

- Qualified to wear respiratory protection
- Not qualified to wear respiratory protection

My evaluation has been based on the following information, as provided to me by the employer.

- A copy of OSHA Standard 29 CFR 1910.120 and appendices.
- A description of the employee's duties as they relate to the employee's exposures.
- A list of known/suspected contaminants and their concentrations (if known).
- A description of any personal protective equipment used or to be used.
- Information from previous medical examinations of the employee which is not readily available to the examining physician.

Part B

I, _____, have examined _____
Physician's Name (print) Participant's Name (print)

And have determined the following information:

**FIGURE 8-3
SUBCONTRACTOR MEDICAL APPROVAL FORM
PAGE TWO**

1. Results of the medical examination and tests (excluding finding or diagnoses unrelated to occupational exposure):

2. Any detected medical conditions which would place the employee at increased risk of material impairment of the employee's health:

3. Recommended limitations upon the employee's assigned work:

I have informed this participant of the results of this medical examination and any medical conditions which require further examination or treatment.

Based on the information provided to me, and in view of the activities and hazard potentials involved at the NAS Pensacola work site, this participant

- May
 May not

Perform his/her assigned task.

Physician's Signature _____

Address _____

Phone Number _____

NOTE: Copies of test results are maintained and available at:

Address

FIGURE 8-4
MEDICAL SURVEILLANCE LETTER

The following statements must be typed on company letterhead and signed by an officer of the company:

LOGO
XYZ CORPORATION
555 E. 5th Street
Nowheresville, Kansas 55555

Month, day, year

Mr. Gerald Walker
Tetra Tech NUS, Inc.
Task Order Manager
1401 Oven Park Drive
Suite 102
Tallahassee, Florida, 32308

Subject: HAZWOPER Training for NAS Pensacola, Pensacola, Florida

Dear Mr. Walker:

As an officer of XYZ Corporation, I hereby state that the persons listed below participate in a medical surveillance program meeting the requirements contained in paragraph (f) of Title 29 of the Code of Federal Regulations (CFR) Part 1910.120, entitled "Hazardous Waste Operations and Emergency Response. I further state that the persons listed below have had physical examinations under this program within the past 12 months and that they have been cleared, by a license physician, to perform hazardous waste site work and to wear positive- and negative-pressure respiratory protection. I also state that, to my knowledge, no person listed below has any medical restriction that would preclude him/her from working at the NAS Pensacola facility.

LIST OF FULL NAMES OF EMPLOYEES AND THEIR SOCIAL SECURITY NUMBERS HERE.

Should you have any questions, please contact me at (555) 555-5555

Sincerely,

(Name and Title of Company Officer)

9.0 SITE CONTROL

This section outlines the means by which TtNUS will delineate work zones and use these work zones in conjunction with decontamination procedures to prevent the spread of contaminants into previously unaffected areas of the site. It is anticipated that a three-zone approach will be used during work at this site: exclusion zone, contamination reduction zone, and support zone. It is also anticipated that this control measure will be used to control access to site work areas. Use of such controls will restrict the general public, minimize potentials for the spread of contaminants and to protect individuals who are not cleared to enter the work areas.

9.1 EXCLUSION ZONE

The exclusion zone will be considered those areas of the site of known or suspected contamination. It is not anticipated that significant amounts of surface contamination are in the proposed work areas of this site. It is anticipated that this will remain so until/unless contaminants are brought to the surface by intrusive activities such as drilling. Furthermore, once such activities have been completed and surface contamination has been removed, the potential for exposure is again diminished and the area can then be reclassified as part of the contamination reduction zone. Therefore, the exclusion zones for this project will be limited to those areas if the site where active work is being performed plus so many feet surrounding the point of operation (See Table 5-1 for specific operation). The exclusion zone for this activity will represent the areas where the soils are disturbed through soil gas surveying and sampling activities. All exclusion zones will be delineated (barrier tape, cones and/or postings) to inform and direct facility personnel.

9.1.1 Exclusion Zone Clearance

A pre-startup site visit will be conducted by members of the field team in an effort to identify proposed subsurface investigation locations, conduct utility clearances, and provide up-front notices concerning scheduled activities within the facility. In all cases, no subsurface activities will proceed without utility clearance. In the event that a utility is struck during a subsurface investigative activity, the emergency numbers provided in Table 2-1 will be notified.

When base personnel are working within the proximity of this investigation, they will be moved or their operation temporarily discontinued to remove them from potential hazards associated with this operation.

9.2 CONTAMINATION REDUCTION ZONE

The contamination reduction zone (CRZ) will be a buffer area between the exclusion zone and any area of the site where contamination is not suspected. This area will also serve as a focal point in supporting exclusion zone activities. This area will be delineated using barrier tape, cones, and postings to inform and direct facility personnel. Decontamination will be conducted at a central location. All equipment potentially contaminated will be bagged and taken to that location for decontamination.

9.3 SUPPORT ZONE

The support zone for this project will include a staging area where site vehicles will be parked, equipment will be unloaded, and where food and drink containers will be maintained. In all cases, the support zones will be established at areas of the site where exposure to site contaminants would not be expected during normal working conditions or foreseeable emergencies.

9.4 SAFE WORK PERMITS

All exclusion zone work conducted in support of this project will be performed using Safe Work Permits to guide and direct field crews on a task by task basis. An example of the Safe Work Permit to be used is illustrated in Figure 9-1. Partially completed Permits for the work to be performed are included in Attachment I. The daily meetings conducted at the site will further support these work permits. This effort will ensure all site-specific considerations and changing conditions are incorporated into the planning effort. All permits will require the signature of the FOL and SSO.

Use of these permits will provide the communication line for reviewing protective measures and hazards associated with each operation. This HASP will be used as the primary reference for selecting levels of protection and control measures. The work permit will take precedence over the HASP when more conservative measures are required based on specific site conditions.

9.5 SITE VISITORS

Site visitors for the purpose of this document are identified as representing the following groups of individuals:

- Personnel invited to observe or participate in operations by TtNUS
- Regulatory personnel (DOD, FDEP, OSHA, etc.)
- Southern Division Navy Personnel
- Other authorized visitors

It is not anticipated that this operation will result in a large number of site visitors. However, as some visitors can reasonably be expected, the following requirements will be enforced:

- All site visitors will be routed to the FOL, who will sign them in to the field logbook. Information to be recorded in the logbook will include the individual's name (proper identification required), who they represent, and purpose for the visit.
- All site visitors will be required to produce the necessary information supporting clearance onto the site. This includes information attesting to applicable training (40-hours of HAZWOPER training required for all Southern Division Navy personnel) and medical surveillance, as stipulated in Section 8 of this document. In addition, to enter the site's operational zones during planned activities, all visitors will be required to first go through site-specific training covering the topics stipulated in Section 8.2 of this document.

NOTE: All site visitors will be escorted at all times while at the site.

Following this, the site visitor will be permitted to enter the site and applicable operational areas. All visitors are required to observe the protective equipment and site restrictions in effect at the area of their visit. Any and all visitors not meeting the requirements as stipulated in this plan for site clearance will not be permitted to enter the site operational zones during planned activities. Any incidence of unauthorized site visitation will cause all onsite activities to be terminated until that visitor can be removed. Removal of unauthorized visitors will be accomplished with support from the Base Contact, if necessary. At a minimum, the Navy Environmental Coordinator will be notified of any unauthorized visitors.

9.6 SITE SECURITY

Site security will be accomplished using TtNUS field personnel. TtNUS will retain complete control over active operational areas. As this activity takes place at Navy facilities open to public access, and along

public highways, the first line of security will take place using traffic permit restrictions, exclusion zone barriers, and any existing barriers at the sites to restrict the general public. The second line of security will take place at the work site referring interested parties to the FOL or designee. The FOL will serve as a focal point for all non-project interested parties, and serve as the final line of security and the primary enforcement contact.

9.7 SITE MAP

Once the areas of contamination, access routes, topography, and dispersion routes are determined, a site map will be generated and adjusted as site conditions change. When possible, these maps will be posted to illustrate up-to-date collection of contaminants and adjustment of zones and access points.

9.8 BUDDY SYSTEM

Personnel engaged in on site activities will practice the "buddy system" to ensure the safety of all personnel involved in this operation.

9.9 MATERIAL SAFETY DATA SHEET (MSDS) REQUIREMENTS

TtNUS and subcontractor personnel will provide MSDSs for all chemicals brought on site. The contents of these documents will be reviewed by the SSO with the user(s) of the chemical substances prior to any actual use or application of the substances on site. A chemical inventory of all chemicals used on site will be developed using the Health and Safety Guidance Manual. The MSDSs will then be maintained in a central location (i.e., temporary office) and will be available for anyone to review upon request.

9.10 COMMUNICATION

As personnel will be working in proximity to one another during field activities, a supported means of communication between field crews members will not be necessary. External communication will be accomplished by using the telephones at predetermined and approved locations. External communication will primarily be used for the purpose of resource and emergency resource communications. Prior to the commencement of activities, the FOL will determine and arrange for telephone communications.

10.0 SPILL CONTAINMENT PROGRAM

10.1 SCOPE AND APPLICATION

It is not anticipated that bulk hazardous materials (over 55-gallons) will be handled at any given time as part of this scope of work. It is also not anticipated that such spillage would constitute a danger to human health or the environment. However, as the job progresses, the potential may exist for accumulating Investigative Derived Wastes (IDW) such as decontamination fluids, soil cuttings, and purge and well development waters, in a central staging area. Once these fluids and other materials have been characterized, they can be removed from this area and properly disposed.

10.2 POTENTIAL SPILL AREAS

Potential spill areas will be periodically monitored in an ongoing attempt to prevent and control further potential contamination of the environment. Currently, limited areas are vulnerable to this hazard including:

- Resource deployment
- Waste transfer
- Central staging

It is anticipated that all IDW generated as a result of this scope of work will be containerized, labeled, and staged to await further analyses. The results of these analyses will determine the method of disposal.

10.3 LEAK AND SPILL DETECTION

To establish an early detection of potential spills or leaks, a periodic walk-around by the personnel staging or disposing of drums or in the resource deployment area will be conducted during working hours to visually determine that storage vessels are not leaking. If a leak is detected, the contents will be transferred, using a hand pump, into a new vessel. The leak will be collected and contained using absorbents such as Oil-Dry, vermiculite, or sand, which are stored at the vulnerable areas in a conspicuously marked drum. This used material, too, will be containerized for disposal pending analysis. All inspections will be documented in the project logbook.

10.4 PERSONNEL TRAINING AND SPILL PREVENTION

All personnel will be instructed in the procedures for incipient spill prevention, containment, and collection of hazardous materials in the site-specific training. The FOL and the SSO will serve as the Spill Response Coordinators for this operation, should the need arise.

10.5 SPILL PREVENTION AND CONTAINMENT EQUIPMENT

The following represents the minimum equipment that may be maintained (depending on anticipated need) at the staging areas at all times for the purpose of supporting this Spill Prevention/Containment Program.

- Sand, clean fill, vermiculite, or other non combustible absorbent (Oil-dry)
- Drums (55-gallon U.S. DOT 17-E or 17-H)
- Shovels, rakes, and brooms
- Container labels

10.6 SPILL CONTROL PLAN

This section describes the procedures the TtNUS field crew members will employ upon the detection of a spill or leak.

1. Notify the SSO or FOL immediately upon detection of a leak or spill. Activate emergency alerting procedures for that area to remove all non-essential personnel.
2. Employ the personal protective equipment stored at the staging area. Take immediate actions to stop the leak or spill by plugging or patching the container or raising the leak to the highest point in the vessel. Spread the absorbent material in the area of the spill, covering it completely.
3. Transfer the material to a new vessel; collect and containerize the absorbent material. Label the new container appropriately. Await analyses for treatment and disposal options.
4. Recontainerize spills, including 2-inch of top cover impacted by the spill. Await test results for treatment or disposal options.

It is not anticipated that a spill will occur that the field crew cannot handle. Should this occur, notification of the appropriate Emergency Response agencies will be carried out by the FOL or SSO in accordance with the procedures discussed in Section 2.0 of this HASP.

11.0 CONFINED-SPACE ENTRY

It is not anticipated, under the proposed scope of work, that confined space and permit-required confined space activities will be conducted. Therefore, personnel under the provisions of this HASP are not allowed, under any circumstances, to enter any confined spaces. A confined space is defined as an area which has one or more of the following characteristics:

- Is large enough and so configured that an employee can bodily enter and perform assigned work.
- Has limited or restricted means for entry or exit (for example, tanks, vessels, silos, storage bins, hoppers, vaults, and pits are spaces that may have limited means of entry).
- Is not designed for continuous employee occupancy.

A Permit-Required Confined Space is one that:

- Contains or has a potential to contain a hazardous atmosphere.
- Contains a material that has the potential to engulf an entrant.
- Has an internal configuration such that an entrant could be trapped or asphyxiated by inwardly converging walls or by a floor which slopes downward and tapers to a smaller cross-section.
- Contains any other recognized, serious, safety or health hazard.

For further information on confined space, consult the Health and Safety Guidance Manual or call the PHSO. If confined space operations are to be performed as part of the scope of work, detailed procedures and training requirements will have to be addressed.

12.0 MATERIALS AND DOCUMENTATION

The TtNUS FOL shall ensure the following materials/documents are taken to the project site and used when required.

- A complete copy of this HASP
- Health and Safety Guidance Manual
- Incident Reports
- Medical Data Sheets
- Material Safety Data Sheets for all chemicals brought on site, including decon solution, fuels, sample preservations, calibration gases, etc.
- Follow-up Reports (to be completed by the FOL)
- A full size OSHA Job Safety and Health Poster
- Training/Medical Surveillance Documentation Form (blank)
- First-Aid Supply Usage Form
- Emergency Reference Form (Section 2.0, extra copy for posting)

12.1 MATERIALS TO BE POSTED AT THE SITE

The following documentation is to be posted or maintained at the site for quick reference purposes. In situations where posting of these documents is not feasible (such as no office trailer), these documents should be filed in a transportable file container and immediately accessible. The file should remain in the FOL's possession.

Chemical Inventory Listing (posted) - This list represents all chemicals brought on site, including decontamination solutions, sample preservatives, fuel, calibration gases, etc.. This list should be posted in a central area.

Material Safety Data Sheets (MSDSs) (maintained) - The MSDSs should also be in a central area accessible to all site personnel. These documents should match all the listings on the chemical inventory list for all substances employed on site. It is acceptable to have these documents within a central folder and the chemical inventory as the table of contents.

The OSHA Job Safety & Health Protection Poster (posted) - This poster, as directed by 29 CFR 1903.2 (a)(1), should be conspicuously posted in places where notices to employees are normally posted. Each FOL shall ensure that this poster is not defaced, altered, or covered by other material.

Site Clearance (maintained) - This is found within the training section of the HASP (See Figure 8-1). This list identifies all site personnel, dates of training (including site-specific training), and medical surveillance and indicates not only clearance but also status. If personnel do not meet these requirements, they do not enter the site while site personnel are engaged in activities.

Emergency Phone Numbers and Directions to the Hospital(s) (maintained) - This list of emergency numbers and hospital directions will be maintained at all phone communications points and in each site vehicle.

Medical Data Sheets/Cards (maintained) - Medical Data Sheets will be filled out by all onsite personnel and filed in a central location. The Medical Data Sheet will accompany any injury or illness requiring medical attention to the medical facility. A copy of this sheet or a wallet card will be given to all personnel to be carried on their person.

Investigative Derived Waste Inventory Log (maintained) – **The FOL and/or the SSO shall log collected containers of IDW. An updated inventory will be submitted to the Base POC at the termination of each shift.**

13.0 GLOSSARY

ACGIH	American Conference of Governmental Industrial Hygienists
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CFR	Code of Federal Regulations
CLEAN	Comprehensive Long-term Environmental Action - Navy
CNS	Central Nervous System
CTO	Contract Task Order
CZR	Contamination Reduction Zone
DOD	United States Department of Defense
eV	electron Volts
FDOT	Florida Department of Transportation
FOL	Field Operations Leader
HASP	Health and Safety Plan
HAZWOPER	Hazardous Waste Operations and Emergency Response
HSM	Health and Safety Manager
IDLH	Immediate Dangerous to Life or Health
IDW	Investigative-Derived Wastes
LEL/LFL	Lower Explosive Limit / Lower Flammable Limit
MSDA	Material Safety Data Sheets
N/A	Not Available
NAS	Naval Air Station
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicity Program
OSHA	Occupational Safety and Health Administration (U.S. Department of Labor)
PEL	Permissible Exposure Limit
PID	Photoionization Detector
PPE	Personal Protective Equipment
SAP	Sampling and Analyses Plan
SOPs	Standard Operating Procedures
SSO	Site Safety Officer
TBD	To be determined
TLV	Threshold Limit Value
TOM	Task Order Manager
TWA	Time-Weighted Average
WP	Work Plan

ATTACHMENT I

**INJURY/ILLNESS PROCEDURE
AND REPORT FORM**

**TETRA TECH NUS, INC.****INJURY/ILLNESS PROCEDURE
WORKER'S COMPENSATION PROGRAM**

WHAT YOU SHOULD DO IF YOU ARE INJURED OR DEVELOP AN ILLNESS AS A RESULT OF YOUR EMPLOYMENT:

- If injury is minor, obtain appropriate first aid treatment.
- If injury or illness is severe or life threatening, obtain professional medical treatment at the nearest hospital emergency room.
- If incident involves a chemical exposure on a project work site, follow instructions in the Health & Safety Plan.
- Immediately report any injury or illness to your supervisor or office manager. In addition, you must contact your Human Resources representative, Marilyn Diethorn at (412) 921-8475, and the Corporate Health and Safety Manager, Matt Soltis at (412) 921-8912 within 24 hours. You will be required to complete an Injury/Illness Report (attached). You may also be required to participate in a more detailed investigation from the Health Sciences Department.
- If further medical treatment is needed, The Hartford Network Referral Unit will furnish a list of network providers customized to the location of the injured employee. These providers are to be used for treatment of Worker's Compensation injuries subject to the laws of the state in which you work. Please call Marilyn Diethorn at (412) 921-8475 for the number of the Referral Unit.

ADDITIONAL QUESTIONS REGARDING WORKER'S COMPENSATION:

Contact your local human resources representative, corporate health and safety coordinator, or Corporate Administration in Pasadena, California, at (626) 351-4664.

Worker's compensation is a state-mandated program that provides medical and disability benefits to employees who become disabled due to job related injury or illness. Tetra Tech, Inc. and its subsidiaries (Tetra Tech or Company) pay premiums on behalf of their employees. The type of injuries or illnesses covered and the amount of benefits paid are regulated by the state worker's compensation boards and vary from state to state. Corporate Administration in Pasadena is responsible for administering the Company's worker's compensation program. The following is a general explanation of worker's compensation provided in the event that you become injured or develop an illness as a result of your employment with Tetra Tech or any of its subsidiaries. Please be aware that the term used for worker's compensation varies from state to state.

WHO IS COVERED:

All employees of Tetra Tech, whether they are on a full-time, part-time or temporary status, working in an office or in the field, are entitled to worker's compensation benefits. All employees must follow the above injury/illness reporting procedures. Consultants, independent contractors, and employees of subcontractors are not covered by Tetra Tech's Worker's Compensation plan.



CASE NO. _____

WHAT IS COVERED:

If you are injured or develop an illness caused by your employment, worker's compensation benefits are available to you subject to the laws of the state you work in. Injuries do not have to be serious; even injuries treated by first aid practices are covered and must be reported. Please note that if you are working out-of-state and away from your home office, you are still eligible for worker's compensation benefits.



**TETRA TECH, INC.
INJURY/ILLNESS REPORT**

Did employee die? Yes No

Was employee performing regular job duties? Yes No

Was safety equipment provided? Yes No

Was safety equipment used? Yes No

Note: Attach any police reports or related diagrams to this accident report.

Witness(es):

Name:

Address:

Telephone:

Describe the Illness or Injury and Part of Body Affected:

Name the Object or Substance which Directly Injured the Employee:

Medical Treatment Required:

No Yes First Aid Only

Physician's Name: _____

Address: _____

Hospital or Office Name: _____

Address: _____

Telephone No.: _____

Lost Work Days:

No. of Lost Work Days _____

Last Date Worked _____

Time Employee Left Work _____

Date Employee Returned to Work _____

No. of Restricted Work Days _____

None

Corrective Action(s) Taken by Unit Reporting the Accident:

Corrective Action Still to be Taken (by whom and when):

Name of Tetra Tech employee the injury or illness was first reported to: _____

Date of Report: _____ **Time of Report:** _____

	Printed Name	Signature	Telephone No.	Date
Project or Office Manager				
Site Safety Coordinator				
Injured Employee				

To be completed by Human Resources:

Date of hire:

Hire date in current job:

Wage information: \$ _____ per _____ (hour, day, week, or month)

Position at time of hire:

Shift hours:

State in which employee was hired:

Status: Full-time Part-time Hours per week: _____ Days per week: _____

Temporary job end date:

To be completed during report to workers' compensation insurance carrier:

Date reported:

Reported by:

TeleClaim phone number:

TeleClaim account number:

Location code:

Confirmation number:

Name of contact:

Field office of claims adjuster:

ATTACHMENT II

**TICK CONTROL
AND
LYME DISEASE**

TICK CONTROL AND LYME DISEASE

The occurrence of Lyme disease has become a worldwide problem since its identification in 1976. This disease is characteristically recognized as being transmitted by ticks, which may be encountered by field personnel while working at this site. As a result, this discussion has been included with this Health and Safety Plan to provide for adequate recognition, evaluation, and control efforts to minimize the occurrence and effects of this potential hazard.

The discovery of Lyme disease is credited to Dr. Allen Steere of Yale University Medical School, and is named after the community where it was (reportedly) first encountered, Lyme, Connecticut. This disease can be transmitted to man through the bite of ticks that are infected with a cork screw-shaped microbe (spirochete). The spread of this disease has been so rapid that in 1984 it surpassed Rocky Mountain Spotted fever as the most common tick-borne disease in the United States. In this country, most of the incidents of this disease have been recorded in the Northeast, and the tick species most commonly attributed with its spread is the deer tick.

Recognition

This hazard potential exists primarily in the spring and summer months, as these are the seasons that tick populations and activity flourish. In fact, 90 percent of the reported cases have occurred from early June through September. Also, this concern exists primarily in heavily vegetated areas. Therefore, recognition of these factors can aid in the awareness and control of this threat.

To aid in the recognition and identification of these insects, an example illustration of the tick species common to the region where this site is located has been included with this discussion. This species (the American Dog tick) is common in the eastern half of the United States, and typically exists in areas covered with grass or underbrush. These insects will attach themselves to animals (including man) that pass through the area and rub against them. After finding a host, the tick inserts its mouthparts and sucks blood until it is fully engorged. This requires a time period of three to twelve days, then the tick will drop off. In addition to Lyme disease concerns, this tick has also been identified as a transmitter of Rocky Mountain Spotted Fever, and the organisms of tularemia and possibly relapsing fever. The wounds left by tick bites can be painful, and can also have a paralyzing effect commonly referred to as tick paralysis.

The earliest symptom of the onset of this disease is the occurrence of an unusual red skin rash. This is commonly the first indication since it has been evidenced that many persons who have contracted this disease were, in fact, unaware that they had been bitten. This rash can appear at the site of the bite anywhere from several days to a few weeks after the bite. It typically starts as a small red spot, and then expands as the spirochetes expand from the bite location. Rash sizes can vary, but have been most commonly associated in a 2 to 3 inch diameter size range. This rash will fade (with or without treatment) after a few weeks. Close inspection is necessary to detect this symptom as the rashes are easy to miss because they're often very faint. Body sites where rashes frequently occur include the thigh areas, groin, and armpits. Also, it is not uncommon for a rash to develop in more than one place.

Other early symptoms include profound fatigue, a stiff neck, and flu-like symptoms such as headache, chills, fever, and muscle aches. Recognition of the onset of any of these symptoms is important since tick bites do not always produce a rash. If left untreated, the disease will progress to its second stage within weeks or months after the infection. This stage involves affects to the heart and nervous system. A common second stage symptom is a paralysis on one or both sides of the face. Others include severe headache, encephalitis, or meningitis. The third and final stage involves the development of chronic inflammatory arthritis, which can occur up to a year or more after the bite.

Evaluation

Evaluation of this hazard potential principally involves field personnel performing close self-inspections for the presence of ticks each time they leave the site. This should involve careful examination, especially of the individuals' heads. Personnel should be aware that when a tick attaches itself to its host, it inserts its entire head under the surface of the skin.

Control

Control of this threat involves several components. First, field personnel must be aware of the climate and area conditions which are commonly associated with being conducive to tick infestation. Second, when working in or walking through potential infested areas, personnel must ensure that they do not have exposed body parts (i.e. at least long sleeved shirts and long pants, particularly when protective coveralls are not worn). In heavily vegetated areas where infestation is likely, Tyvek coveralls will be required to minimize this hazard potential. Also, several commercial products have been demonstrated as being effective in repelling ticks. Examples include Permanone, Off!, and Cutter. These types of repellents will be used at the direction and discretion of the Tetra Tech NUS Health and Safety Officer, and only in accordance and observation of manufacturer's recommendations. In most instances, however, such repellents are typically applied to the outside surfaces of clothing (and not directly onto the skin), and should be applied also to shoe tops, socks, pants cuffs, and other areas most susceptible to ticks.

Tick Removal

In the event that a tick is discovered to be attached to a member of the field team, timely removal of the insect is critical to reducing the potential for contracting the disease. According to available information and research, there is apparently a grace period of at least a few hours from the time of the bite before the tick transmits the microbe (the spirochetes are not present in the mouth parts of the tick). However, the incident of a tick bite is frequently unnoticed, and the discovery of the tick may not occur until after this suspected grace period has already elapsed. Therefore, timely removal is very important. The preferred method of tick removal is to pull it out using tweezers or small forceps. In this method, the tick should be grasped as close to the mouth as possible, and then pulled steadily upward. Care must be exercised so as not to pull in a jerking motion as this can result in the head becoming detached. After the tick has been removed, disinfect the bite with rubbing alcohol or povidone iodine (Betadine). The tick must not be handled as the microbes can enter the body through any breaks in intact skin. The bite should be checked occasionally for at least a two-week period to see if a rash forms. If it does, medical attention must be promptly sought.

In order to provide for proper and timely response to the occurrence of a tick bite, the SSO will ensure that the site First Aid kit is properly equipped with medical forceps and rubbing alcohol, in addition to the standard kit contents. Also, an adequate supply of commercial insect (tick) repellents will be maintained on-site, and all personnel will be trained in its proper application and will be required to use it, at the direction of FOL.

ATTACHMENT III

EQUIPMENT INSPECTION CHECKLIST

EQUIPMENT INSPECTION

COMPANY: _____ **UNIT NO.** _____

FREQUENCY: Inspect daily, document prior to use and as repairs are needed.

Inspection Date: ____/____/____ Time: _____ Equipment Type: _____

	(e.g., bulldozer)		
	Good	Need Repair	N/A
Tires or tracks	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hoses and belts	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Cab, mirrors, safety glass	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Turn signals, lights, brake lights, etc. (front/rear) for equipment approved for highway use?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Is the equipment equipped with audible back-up alarms and back-up lights?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Horn and gauges	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Brake condition (dynamic, park, etc.)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Fire extinguisher (Type/Rating - _____)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Fluid Levels:			
- Engine oil	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Transmission fluid	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Brake fluid	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Cooling system fluid	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Windshield wipers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
- Hydraulic oil	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Oil leak/lube	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Coupling devices and connectors	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Exhaust system	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Blade/boom/ripper condition	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Accessways: Frame, hand holds, ladders, walkways (non-slip surfaces), guardrails?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Power cable and/or hoist cable	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Steering (standard and emergency)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Safety Guards:

	Yes	No
- Around rotating apparatus (belts, pulleys, sprockets, spindles, drums, flywheels, chains) all points of operations protected from accidental contact? _____	<input type="checkbox"/>	<input type="checkbox"/>
- Hot pipes and surfaces exposed to accidental contact? _____	<input type="checkbox"/>	<input type="checkbox"/>
- All emergency shut offs have been identified and communicated to the field crew? _____	<input type="checkbox"/>	<input type="checkbox"/>
- Have emergency shutoffs been field tested? _____	<input type="checkbox"/>	<input type="checkbox"/>
- Results? _____	<input type="checkbox"/>	<input type="checkbox"/>
- Are any structural members bent, rusted, or otherwise show signs of damage? _____	<input type="checkbox"/>	<input type="checkbox"/>
- Are fueling cans used with this equipment approved type safety cans? _____	<input type="checkbox"/>	<input type="checkbox"/>

- Have the attachments designed for use (as per manufacturer's recommendation) with this equipment been inspected and are considered suitable for use? _____

Portable Power Tools:

- Tools and Equipment in Safe Condition? _____
- Saw blades, grinding wheels free from recognizable defects (grinding wheels have been sounded)? _____
- Portable electric tools properly grounded? _____
- Damage to electrical power cords? _____
- Blade guards in place? _____
- Components adjusted as per manufacturers recommendation? _____

Cleanliness:

- Overall condition (is the decontamination performed prior to arrival on-site considered acceptable)? _____
- Where was this equipment used prior to its arrival on site? _____
- Site Contaminants of concern at the previous site? _____
- Inside debris (coffee cups, soda cans, tools and equipment) blocking free access to foot controls? _____

Operator Qualifications (as applicable for all heavy equipment):

- Does the operator have proper licensing where applicable, (e.g., CDL)? _____
- Does the operator, understand the equipments operating instructions? _____
- Is the operator experienced with this equipment? _____
- Does the operator have emotional and/or physical limitations which would prevent him/her from performing this task in a safe manner? _____
- Is the operator 21 years of age or more? _____

Identification:

- Is a tagging system available, for positive identification, for tools removed from service? _____

Additional Inspection Required Prior to Use On-Site

- | | Yes | No |
|--|--------------------------|--------------------------|
| - Does equipment emit noise levels above 90 decibels? | <input type="checkbox"/> | <input type="checkbox"/> |
| - If so, has an 8-hour noise dosimetry test been performed? | <input type="checkbox"/> | <input type="checkbox"/> |
| - Results of noise dosimetry: _____ | | |
| - Defects and repairs needed: _____ | | |
| - General Safety Condition: _____ | | |
| - Operator or mechanic signature: _____ | | |
| Approved for Use: <input type="checkbox"/> Yes <input type="checkbox"/> No | | |

Site Safety Officer Signature

ATTACHMENT IV

SAFE WORK PERMITS

ATTACHMENT V

HEAT STRESS

HEAT STRESS

Because some physically demanding field work is expected to take place during warmer months or periods, heat related disorders are a potential problem. Discussed below are the common heat-related disorders and the recommended actions to prevent heat stress.

Heat Related Disorders

Heat Rash

Also known as prickly heat, this condition affects the skin. It occurs in situations where the skin remains wet most of the time. The sweat ducts become plugged and a skin rash soon appears.

Signs and Symptoms

- Skin rash will appear on affected areas of the body.
- Tingling or prickling sensation will be felt on the affected areas.

Heat Cramps

Heat cramps are muscle pains, usually in the lower extremities, the abdomen, or both, that occur after profuse sweating with accompanying salt depletion. Heat cramps most often afflict people in good physical condition, who overwork in conditions of high temperature and humidity. Untreated, heat cramps may progress to heat exhaustion.

Signs and Symptoms

- Cramps in the extremities and abdomen that begin suddenly during vigorous activity. Heat cramps can be mild with only slight abdominal cramping and tingling in the extremities, but more commonly present intense and incapacitating pain in the abdomen and extremities.
- Respiration rate will increase, decreasing after the pain subsides.
- Pulse rate will increase
- Skin will be pale and moist.
- Body temperature will be normal
- Generalized weakness will be noted as the pain subsides.
- Loss of consciousness and airway maintenance are seldom problems with this condition.

Treatment for heat cramps is aimed at eliminating the exposure and restoring the loss of salt and water.

Heat Exhaustion

Heat exhaustion is a more severe response to salt and water loss, as well as an initial disturbance in the body's heat-regulations system. Like heat cramps, heat exhaustion tends to occur in people working in hot environments. Heat exhaustion may progress to heat stroke. Treatment for heat exhaustion is similar in principle to that for heat cramps.

Signs and Symptoms

- Heat exhaustion may be accompanied present by a headache, fatigue, dizziness, or nausea with occasional abdominal cramping. More severe cases of heat exhaustion may resulting partial or complete temporary loss of respiration nd circulation due to cerebral ischemia.
- Sweating will be profuse.
- Pulse rate will be rapid and weak.
- Respiration rate will be rapid and shallow.
- The skin will be pale and clammy
- The body temperature will be normal or decreased.
- The person could be irritable and restless.

Heat Stroke

Heat stroke is caused by a severe disturbance in the body's heat-regulating system and is a profound emergency: The mortality rate ranges from 25 to 50 percent. It is most common in men over 40, especially alcoholics. It can also occur to people of any age having too much exposure to the sun or prolonged confinement in a hot atmosphere. Heat stroke comes on suddenly. As the sweating mechanism fails, the body temperature begins to rise precipitously, reaching 106°F (41°C) or higher within 10 to 15 minutes. If the situation is not corrected rapidly, the body cells -- especially have very vulnerable cells to the brain--are literally cooked, and the central nervous system is irreversibly damaged. The treatment for heat stroke is aimed at maintaining vital functions and causing as rapid a decrease of body temperature as possible.

Signs and Symptoms

- The person's pulse will be strong and bounding.
- The skin will be hot, dry, and flushed.
- The worker may experience headache, dizziness, and dryness of mouth
- Seizures and coma can occur.
- Loss of consciousness and airway maintenance problems can occur.

These are only guidelines for heat related emergencies. Actual training in emergency medical care or basic first aid is recommended.

Controlling Heat Stress

The SSO shall visually monitor personnel to note for signs of heat stress. Field personnel will also be instructed to observe for symptoms of heat stress and methods on how to control it. One or more of the following control measures can be used to help control heat stress:

- Provide adequate liquids to replace lost body fluids. Personnel must replace water and salt lost from sweating. Personnel must be encouraged to drink more than the amount required to satisfy thirst. Thirst satisfaction is not an accurate indicator of adequate salt and fluid replacement.
- Replacement fluids can be commercial mixes such as Gatorade®.
- Establish a work regime that will provide adequate rest periods for cooling down. This may require additional shifts of workers.

- Cooling devices such as vortex tubes or cooling vests can be worn beneath protective garments.
- Breaks are to be taken in a cool rest area (77°F is best).
- Personnel shall remove impermeable protective garments during rest periods.
- Personnel shall not be assigned other tasks during rest periods.
- Personnel shall be informed of the importance of adequate rest, acclimation, and proper diet in the prevention of heat stress.

The heat stress of personnel onsite may be monitored utilizing biological monitoring.

One of the following biological monitoring procedures may be utilized by the SSO to monitor heat stress concerns.

- Heart rate (HR) shall be measured by the pulse for 30 seconds as early as possible in the resting period. The HR at the beginning of the rest period should not exceed 110 beats/minute. If the HR is higher, the next work period should be shortened by 10 minutes (or 33 percent), while the length of rest period stays the same. If the pulse rate is 100 beats/minute at the beginning of the next rest period, the following work cycle should be shortened by 33 percent. The length of the initial work period will be determined by using the table below.

PERMISSIBLE HEAT EXPOSURE THRESHOLD LIMIT VALUES

<u>Work-Rest Regimen</u>	<u>Work Load</u>		
	<u>Light</u>	<u>Moderate</u>	<u>Heavy</u>
Continuous	80.0°F	80.0°F	77.0°F
75% Work - 25% Rest, Each Hour	87.0°F	82.4°F	78.6°F
50% Work - 50% Rest, Each Hour	88.5°F	85.0°F	82.2°F
25% Work - 75% Rest, Each Hour	90.0°F	88.0°F	86.0°F

- Body temperature shall be measured orally with a clinical thermometer as early as possible in the resting period. Oral temperature at the beginning of the rest period should not exceed 99°F. If it does, the next work period should be shortened by 10 minutes (or 33 percent), while the length of the rest period stays the same. However, if the oral temperature exceeds 99.7°F at the beginning of the next rest period, the following work cycle shall be further shortened by 33 percent. OT should be measured at the end of the rest period to make sure that it has dropped below 99°F. At no time shall work begin with the oral temperature above 99°F.

NOTE: External temperatures in excess of those stated above shall be regarded as inclement weather. Work continuation, termination, or alteration of the work schedule will be at the discretion of the FOL or SSO.

SAFE WORK PERMIT DECONTAMINATION ACTIVITIES

Permit No. _____ Date: _____ Time: From _____ to _____

SECTION I: General Job Scope

- I. Work limited to the following (description, area, equipment used): Decontamination of sampling equipment. Brushes and spray bottles will be used to decon small sampling equipment.
- II. Required Monitoring Instrument(s): None required
- III. Field Crew: _____
- IV. On-site Inspection conducted Yes No Initials of Inspector TtNUS

SECTION II: General Safety Requirements (To be filled in by permit issuer)

- | | |
|--|---|
| IV. Protective equipment required | Respiratory equipment required |
| Level D <input checked="" type="checkbox"/> Level B <input type="checkbox"/> | Full face APR <input type="checkbox"/> Escape Pack <input type="checkbox"/> |
| Level C <input type="checkbox"/> Level A <input type="checkbox"/> | Half face APR <input type="checkbox"/> SCBA <input type="checkbox"/> |
| Detailed on Reverse | SAR <input type="checkbox"/> Bottle Trailer <input type="checkbox"/> |
| | Skid Rig <input type="checkbox"/> None <input checked="" type="checkbox"/> |

Modifications/Exceptions: Minimum requirement include sleeved shirt and long pants, safety glasses, and nitrile gloves.

- | | | |
|--|---|---|
| V. Chemicals of Concern | Action Level(s) | Response Measures |
| <u>Potential site contaminants include VOCs and SVOCs from petroleum compounds</u> | <u>Sustained readings above background are not expected in worker breathing zones</u> | <u>Suspend site activities and retreat to an unaffected area.</u> |

- | | | |
|--|---|---|
| VI. Additional Safety Equipment/Procedures | | |
| Hard-hat..... | <input type="checkbox"/> Yes <input type="checkbox"/> No | Hearing Protection (Plugs/Muffs) <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Safety Glasses | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No | Safety belt/harness <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Chemical/splash goggles | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Radio <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Splash Shield..... | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Barricades <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Splash suits/coveralls..... | <input type="checkbox"/> Yes <input type="checkbox"/> No | Gloves (Type - <u>Nitrile</u>) <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| Steel toe Work shoes or boots | <input type="checkbox"/> Yes <input type="checkbox"/> No | Work/rest regimen <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |

Modifications/Exceptions: PVC rain suits or PE or PVC coated Tyvek for protection against splashes and overspray. Chemical resistant boot covers if excessive liquids are generated or protected footwear.

- | | | | |
|---|-------------------------------------|-------------------------------------|---|
| VII. Procedure review with permit acceptors | Yes | NA | |
| Safety shower/eyewash (Location & Use) | <input checked="" type="checkbox"/> | <input type="checkbox"/> | Emergency alarms..... <input checked="" type="checkbox"/> <input type="checkbox"/> |
| Procedure for safe job completion..... | <input type="checkbox"/> | <input checked="" type="checkbox"/> | Evacuation routes..... <input checked="" type="checkbox"/> <input type="checkbox"/> |
| Contractor tools/equipment/PPE inspected..... | <input type="checkbox"/> | <input checked="" type="checkbox"/> | Assembly points..... <input checked="" type="checkbox"/> <input type="checkbox"/> |

- | | | | |
|---|--------------------------|--------------------------|-------------------------------------|
| VIII. Site Preparation | Yes | No | NA |
| Utility Locating and Excavation Clearance completed..... | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| Vehicle and Foot Traffic Routes Cleared and Established | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| Physical Hazards Barricaded and Isolated..... | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| Emergency Equipment Staged..... | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

- IX. Additional Permits required (Hot work, confined space entry, excavation etc.) Yes No
If yes, complete permit required or contact Health Sciences, Pittsburgh Office

- X. Special instructions, precautions: Chemical hazards with decontamination because of use of fluids such as isopropyl alcohol, methanol, etc. To minimize the potential for exposure, site personnel will use PPE and prevent contact with potentially contaminated equipment. Refer to the manufacturer's MSDS regarding PPE, handling, storage, and first-aid measures related to decontamination fluids.

Permit Issued by: _____ Permit Accepted by: _____

**SAFE WORK PERMIT FOR
SOIL BORINGS AND WELL INSTALLATION**

Permit No. _____ Date: _____ Time: From _____ to _____

SECTION I: General Job Scope

I. Work limited to the following (description, area, equipment used): Soil borings using Direct Push Technology (i.e., Geoprobe) technique. Monitoring well installation is included in this task.

II. Required Monitoring Instruments: FID or PID

III. Field Crew: _____

IV. On-site Inspection conducted Yes No Initials of Inspector TtNUS

SECTION II: General Safety Requirements (To be filled in by permit issuer)

IV. Protective equipment required	Respiratory equipment required	
Level D <input checked="" type="checkbox"/> Level B <input type="checkbox"/>	Full face APR <input type="checkbox"/>	Escape Pack <input type="checkbox"/>
Level C <input type="checkbox"/> Level A <input type="checkbox"/>	Half face APR <input type="checkbox"/>	SCBA <input type="checkbox"/>
Detailed on Reverse	SKA-PAC SAR <input type="checkbox"/>	Bottle Trailer <input type="checkbox"/>
	Skid Rig <input type="checkbox"/>	None <input checked="" type="checkbox"/>

Modifications/Exceptions: Minimum requirement include sleeved shirt and long pants, safety shoes, safety glasses, hardhat, hearing protection, and nitrile gloves or leather gloves with surgical-style inner gloves.

V. Chemicals of Concern	Action Level(s)	Response Measures
<u>Potential site contaminants include VOCs and SVOCs from petroleum compounds</u>	<u>Any sustained readings above background in worker breathing zones.</u>	<u>Suspend site activities and retreat to an unaffected area.</u>

VI. Additional Safety Equipment/Procedures		
Hard-hat.....	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Hearing Protection (Plugs/Muffs) <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Safety Glasses	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Safety belt/harness <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Chemical/splash goggles.....	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Radio <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Splash Shield.....	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Barricades <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Splash suits/coveralls	<input type="checkbox"/> Yes <input type="checkbox"/> No	Gloves (Type _____) <input type="checkbox"/> Yes <input type="checkbox"/> No
Steel toe Work shoes or boots	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Work/rest regimen <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

Modifications/Exceptions: Reflective vests for high traffic areas. Tyvek coverall and impermeable boots if there is a potential for soiling work clothes.

VII. Procedure review with permit acceptors	Yes	NA	Emergency alarms.....	Yes	NA
Safety shower/eyewash (Location & Use)	<input type="checkbox"/>	<input type="checkbox"/>	Evacuation routes	<input type="checkbox"/>	<input type="checkbox"/>
Procedure for safe job completion.....	<input type="checkbox"/>	<input type="checkbox"/>	Assembly points.....	<input type="checkbox"/>	<input type="checkbox"/>
Contractor tools/equipment/PPE inspected.....	<input type="checkbox"/>	<input type="checkbox"/>			

VIII. Equipment Preparation	Yes	NA
Equipment drained/depressurized.....	<input type="checkbox"/>	<input type="checkbox"/>
Equipment purged/cleaned	<input type="checkbox"/>	<input type="checkbox"/>
Isolation checklist completed	<input type="checkbox"/>	<input type="checkbox"/>
Electrical lockout required/field switch tested.....	<input type="checkbox"/>	<input type="checkbox"/>
Blinds/misalignments/blocks & bleeds in place.....	<input type="checkbox"/>	<input type="checkbox"/>
Hazardous materials on walls/behind liners considered	<input type="checkbox"/>	<input type="checkbox"/>

IX. Additional Permits required (Hot work, confined space entry, excavation etc.)..... Yes No
If yes, complete permit required or contact Health Sciences, Pittsburgh Office

X. Special instructions, precautions: Minimize generation of airborne dusts.

Permit Issued by: _____ Permit Accepted by: _____

**SAFE WORK PERMIT FOR
SOIL BORINGS AND WELL INSTALLATION**

SAFE WORK PERMIT FOR MOBILIZATION/DEMobilIZATION

Permit No. _____ Date: _____ Time: From _____ to _____

SECTION I: General Job Scope

- I. Work limited to the following (description, area, equipment used): Mobilization/Demobilization
- II. Names: _____
- III. Onsite Inspection conducted Yes No Initials of Inspector TtNUS

SECTION II: General Safety Requirements (To be filled in by permit issuer)

- | | |
|--|---|
| IV. Protective equipment required
Level D <input checked="" type="checkbox"/> Level B <input type="checkbox"/>
Level C <input type="checkbox"/> Level A <input type="checkbox"/> | Respiratory equipment required
Full face APR <input type="checkbox"/> Escape Pack <input type="checkbox"/>
Half face APR <input type="checkbox"/> SCBA <input type="checkbox"/>
SAR <input type="checkbox"/> Bottle Trailer <input type="checkbox"/>
Skid Rig <input type="checkbox"/> None <input checked="" type="checkbox"/> |
|--|---|

Modifications/Exceptions: Sleeved shirts and long pants, safety footwear,

V. Chemicals of Concern	Action Level(s)	Response Measures
<u>None anticipated given the nature of activities and limited contact w/media</u>	<u>None</u>	
_____	_____	_____
_____	_____	_____

- VI. Additional Safety Equipment/Procedures
- | | |
|--|---|
| Hardhat <input type="checkbox"/> Yes <input type="checkbox"/> No | Hearing Protection (Plugs/Muffs) <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Safety Glasses <input type="checkbox"/> Yes <input type="checkbox"/> No | Safety belt/harness <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Chemical/splash goggles <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Radio <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Splash Shield <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Barricades <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Splash suit/coveralls (Type) <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Gloves (leather/cotton) <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| Steel toe work boots <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No | Work/rest regimen <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Chemical Protective Over-boots <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | |
- Modifications/Exceptions: Safety glasses, hardhat, reflective vests, and hearing protection when required.

- | | |
|--|--|
| VII. Procedure review with permit acceptors
Safety shower/eyewash (Location & Use) <input type="checkbox"/> Yes <input checked="" type="checkbox"/> NA
Procedure for safe job completion <input type="checkbox"/> Yes <input checked="" type="checkbox"/> NA
Contractor tools/equipment inspected <input type="checkbox"/> Yes <input checked="" type="checkbox"/> NA | Emergency alarms <input checked="" type="checkbox"/> Yes <input type="checkbox"/> NA
Evacuation routes <input checked="" type="checkbox"/> Yes <input type="checkbox"/> NA
Assembly points <input checked="" type="checkbox"/> Yes <input type="checkbox"/> NA |
|--|--|

- | |
|---|
| VII. Site Preparation
Utility Locating and Excavation Clearance completed <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA
Vehicle and Foot Traffic Routes Cleared and Established <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA
Physical Hazards Barricaded and Isolated <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA
Emergency Equipment Staged <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> NA |
|---|

- VIII. Additional Permits required (Hot work, confined space entry, excavation, etc.). Yes No
If yes, See SSO for appropriate permit

- IX. Special instructions, precautions: _____
- _____
- _____

Permit Issued by: _____ Permit Accepted by: _____

SAFE WORK PERMIT FOR MULTI-MEDIA SAMPLING

Permit No. _____ Date: _____ Time: From _____ to _____

SECTION I: General Job Scope

- I. Work limited to the following (description, area, equipment used): Multi-media sampling including groundwater (including natural attenuation), soil, and IDW sampling.
- II. Required Monitoring Instrument(s): PID or FID
- III. Field Crew: _____
- IV. On-site Inspection conducted Yes No Initials of Inspector TtNUS

SECTION II: General Safety Requirements (To be filled in by permit issuer)

- | | |
|--|--|
| IV. Protective equipment required | Respiratory equipment required |
| Level D <input checked="" type="checkbox"/> Level B <input type="checkbox"/> | Full face APR <input type="checkbox"/> Escape Pack <input type="checkbox"/> |
| Level C <input type="checkbox"/> Level A <input type="checkbox"/> | Half face APR <input type="checkbox"/> SCBA <input type="checkbox"/> |
| Detailed on Reverse | SKA-PAC SAR <input type="checkbox"/> Bottle Trailer <input type="checkbox"/> |
| | Skid Rig <input type="checkbox"/> None <input checked="" type="checkbox"/> |

Modifications/Exceptions: Minimum requirement include sleeved shirt and long pants, safety shoes, surgical style gloves, and safety glasses. Hard hats and hearing protection will be worn when working near operating equipment or when required by the SSO.

- | | | |
|----------------------------------|-----------------------------------|---------------------------------------|
| V. Chemicals of Concern | Action Level(s) | Response Measures |
| <u>Site contaminants include</u> | <u>Any sustained readings</u> | <u>Suspend site activities and</u> |
| <u>VOCs and SVOCs</u> | <u>above background</u> | <u>retreat to an unaffected area.</u> |
| <u>from petroleum compounds</u> | <u>in worker breathing zones.</u> | |

- | | | | | | |
|--|---|--|----------------------------------|---|--|
| VI. Additional Safety Equipment/Procedures | | | | | |
| Hard-hat..... | <input type="checkbox"/> Yes | <input type="checkbox"/> No | Hearing Protection (Plugs/Muffs) | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Safety Glasses | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No | Safety belt/harness | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No |
| Chemical/splash goggles..... | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No | Radio | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No |
| Splash Shield..... | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No | Barricades | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No |
| Splash suits/coveralls | <input type="checkbox"/> Yes | <input type="checkbox"/> No | Gloves (Type - Nitrile) | <input checked="" type="checkbox"/> Yes | <input type="checkbox"/> No |
| Steel toe Work shoes or boots | <input checked="" type="checkbox"/> Yes | <input type="checkbox"/> No | Work/rest regimen | <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No |
- Modifications/Exceptions: Reflective vests for high traffic areas. Tyvek coverall if there is a potential for soiling work cloths. SSO may dictate double-layering gloves.

- | | | | | | |
|--|--------------------------|--------------------------|-------------------------|--------------------------|--------------------------|
| VII. Procedure review with permit acceptors | Yes | NA | | Yes | NA |
| Safety shower/eyewash (Location & Use) | <input type="checkbox"/> | <input type="checkbox"/> | Emergency alarms | <input type="checkbox"/> | <input type="checkbox"/> |
| Procedure for safe job completion | <input type="checkbox"/> | <input type="checkbox"/> | Evacuation routes | <input type="checkbox"/> | <input type="checkbox"/> |
| Contractor tools/equipment/PPE inspected | <input type="checkbox"/> | <input type="checkbox"/> | Assembly points..... | <input type="checkbox"/> | <input type="checkbox"/> |

- | | | |
|---|--------------------------|--------------------------|
| VIII. Equipment Preparation | Yes | NA |
| Equipment drained/depressurized..... | <input type="checkbox"/> | <input type="checkbox"/> |
| Equipment purged/cleaned | <input type="checkbox"/> | <input type="checkbox"/> |
| Isolation checklist completed | <input type="checkbox"/> | <input type="checkbox"/> |
| Electrical lockout required/field switch tested..... | <input type="checkbox"/> | <input type="checkbox"/> |
| Blinds/misalignments/blocks & bleeds in place..... | <input type="checkbox"/> | <input type="checkbox"/> |
| Hazardous materials on walls/behind liners considered | <input type="checkbox"/> | <input type="checkbox"/> |

- IX. Additional Permits required (Hot work, confined space entry, excavation etc.)..... Yes No
If yes, complete permit required or contact Health Sciences, Pittsburgh Office
- X. Special instructions, precautions: _____

Permit Issued by: _____ Permit Accepted by: _____

**SAFE WORK PERMIT FOR
MULTI-MEDIA SAMPLING**